3SBH1231A2 ✔ ACTIVE


CII | CII 3SBH Relay

TE Internal #: 2-1617076-6

General Purpose Signal Relay, DC, Non-Polarized, Monostable, 4 Form C 4PDT-CO, 2 A Contact Rating, 26.5 VDC Coil Voltage, CII 3SBH Relay

View on TE.com >

Relays & Contactors > Electromechanical Relays > 4PDT Signal Relay: Electrically-Held, With Coil Suppression



Relay & Contactor Type: **General Purpose Signal Relay**

Coil Magnetic System: **Non-Polarized, Monostable**

Contact Arrangement: **4 Form C 4PDT-CO**

Current Type: **DC**

Contact Current Rating: **2 A**

All 4PDT Signal Relay: Electrically-Held, With Coil Suppression (26)

Features

Product Type Features

Relay & Contactor Type	General Purpose Signal Relay

Configuration Features

Coil Special Features	Coil Suppression Diode
Contact Arrangement	4 Form C 4PDT-CO

Electrical Characteristics

Coil Resistance	720 Ω
Contact Current Rating	2 A
Coil Voltage Rating	26.5 VDC
Coil Power Rating DC	.975 W

Body Features

Enclosure Type	Hermetically Sealed

Termination Features

Main Termination & Connection Type	Solder Pins
Coil Termination & Connection Type	Solder Pins

Mechanical Attachment

Product Mount Type	Board Mount

Usage Conditions

Operating Temperature Range	-65 – 125 °C
Environmental Ambient Temperature (Max)	125 °C[257 °F]

Operation/Application

Vibration Resistance	30G's, 10 – 3000Hz
Shock Resistance	75G's, 6ms
Coil Magnetic System	Non-Polarized, Monostable
Current Type	DC

Other

Contact Current Class	≤2 A
Coil Power Rating Class	>.6 – ≤1 W

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量超出标准 Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not lead free process capable

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for

substances in articles'(Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.


Compatible Parts



TE Part # CAT-3SBC-DPDT-WCS
DPDT Signal Relay: Electrically-Held, With Coil Suppression



TE Part # 1-1617562-8
3SBC2057A2=M39016/13-112P




TE Part # CAT-3SBC-DPDT-WOCS
DPDT Relay : Electrically-Held, 1/5-Size Relay

Also in the Series | CII 3SBH Relay




PCB Relays(14)

Customers Also Bought



TE Part #216296-002
22759/32-18-9



TE Part #34321
SPLICE,SOLIS BUTT 8



TE Part #53405-1
PIDG PVF2 22-16COMM 22-18MIL 4




TE Part #66099-4
III+ PIN,1-16,30AU/FL,LP




TE Part #9-146261-0
80 MODII HDR DRST B/A .100CL LF



TE Part #207684-5
AMPLIMITE,SKT CONT,SZ 22




TE Part #2-1617754-1
FCA-410-1622M=M83536/16-022M



TE Part #8-1617760-3
FCB-405-0622M=M83536/6-022M



TE Part #4-1630019-9
HSC200 R75 5%



TE Part #5103310-2
A/L LOW PRO HDR 14P RA BLACK

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-1617076-6_F.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-1617076-6_F.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-1617076-6_F.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages

RELAY

English