



Connectors > Rectangular Connectors > Standard Rectangular Connectors > STD Temp GRACE INERTIA Plug



Connector Product Type: **Housing**
Connector & Housing Type: **Plug**
Termination Method to Wire & Cable: **Crimp**
Connector System: **Wire-to-Wire**
Contact Retention Within Housing: **Without**

[All STD Temp GRACE INERTIA Plug \(25\)](#)

Features

Product Type Features

Connector Product Type	Housing
Connector & Housing Type	Plug
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	1
Number of Rows	1

Electrical Characteristics

Operating Voltage	600 VDC
-------------------	---------

Body Features

Primary Product Color	Natural
-----------------------	---------



Contact Features

Multiple Contact Types	Without
Contact Retention Within Housing	Without
Contact Type	Receptacle

Termination Features

Termination Method to Wire & Cable	Crimp
------------------------------------	-------

Mechanical Attachment

Connector Mounting Type	Panel Mount
-------------------------	-------------

Housing Features

Housing Material	Nylon 66
------------------	----------

Dimensions

Connector Width	13.5 mm
-----------------	---------

Usage Conditions

Operating Temperature Range	-30 – 105 °C[-22 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Identification Marking

Circuit Identification Feature	Without
--------------------------------	---------

Industry Standards

UL Flammability Rating	UL 94V-0
Glow Wire Rating	Standard Part - Not Glow Wire

Packaging Features

Packaging Quantity	500
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250)



Candidate List Declared Against: JUNE 2025 (250)
Does not contain REACH SVHC

Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # CAT-G7534-R2435
GRACE INERTIA Receptacle

Also in the Series | GRACE INERTIA 6.2

Connector Contacts(4)


Connector Hardware(1)

Power Contacts(4)

Rectangular Connector Housings(13)



Rectangular Power Connectors(13)




Standard Rectangular Connectors(13)



Wire-to-Board Connector Assemblies & Housings(5)

Customers Also Bought



TE Part #170338-1
AMP-IN 22-18 AWG




TE Part #177911-1
POWER DBL LOCK CAP HSG P/M 9P




TE Part #179862-1
AMP POWER D/LOCK PLUG HSG 6P



TE Part #316063-1
POWER DBL LOCK PLATE 4P /6.5MM



TE Part #353255-1
110 HSG. PL EX REC. 7.6mm 3P NAT




TE Part #353256-1
110 HSG. PL EX REC. 7.6mm 3P NAT




TE Part #8-1241961-2
STD TIM HOUSING MKII 2POS



TE Part #8-1241965-2
STD TIMER PLUG HSG 2P W/EXT. LOCKING



TE Part #1746974-1
GRACE INERTIA CONNECTOR 6.2 MM PITCH TAB



TE Part #1-172127-1
FF 250 REC HSG 1P NYLON NAT

Documents

Product Drawings

GIC 6.2MM PITCH 1POS PLUG HSG

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_4-1903683-1_F_c-4-1903683-1-f.2d_dxf.zip



English

Customer View Model

[ENG_CVM_CVM_4-1903683-1_F_c-4-1903683-1-f.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_4-1903683-1_F_c-4-1903683-1-f.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English