41829 ✔ ACTIVE


FASTON | FASTON 250

TE Internal #: 41829

Quick Disconnect Receptacle, Uninsulated, 14 – 12 AWG, 2.1 – 3.31 mm² Wire, 6.35 mm [.25 in] Tab Width, F-Crimp, Straight, Brass, FASTON 250

View on TE.com >

Terminals & Splices > Quick Disconnects







Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **2.1 – 3.31 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable

Mechanical Attachment

Wire Insulation Support	With

Dimensions

Product Length	20.7 mm[.815 in]
Compatible Insulation Diameter Range	2.79 – 5.33 mm[.11 – .21 in]
Terminal Material Thickness	.46 mm[.018 in]
Wire Size	2.1 – 3.31 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	CSA, UL

Packaging Features

Packaging Quantity	1000
Packaging Method	Loose Piece/Carton

Other

Line	Premier

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




TE Part # 58525-1
PROCRIMPER TOOL & DIE



TE Part # 58525-2
PROCRIMPER DIE



TE Part # 90120
DAHT 250 FASTON REC 14-10 ASSY




TE Part # 61873-1
250 FASTON REC 18-14 AWG TPBR

Also in the Series | FASTON 250




Compression Connectors(4)



Crimp Terminal Housings(117)



Insulation Boots & Sleeves(16)



Magnet Wire Terminals(1)



PCB Terminals(133)



Quick Disconnects(412)




Splices(4)

Customers Also Bought


Quick Disconnect Receptacle, Uninsulated, 14 – 12 AWG, 2.1 – 3.31 mm² Wire, 6.35 mm [.25 in] Tab Width, F-Crimp, Straight, Brass, FASTON 250



TE Part #41729
250 FASTON REC 18-16 AWG TPBR



TE Part #63950-1
250 FASTON TAB TPBR



TE Part #63994-1
FASTON 205/250 PCB MOUNTED TPBR



TE Part #170354-1
LOW PROFILE E.I. CONNECTOR



TE Part #170887-3
IS SHUR PLG 5 DIA NAT




TE Part #171825-5
5 POS EIS POST HDR




TE Part #171826-5
POST HDR ASSY HDR AMP EI CONN



TE Part #172142-2
EIS LOW PROFILE HSG 2P NATURAL



TE Part #172510-1
MIC CAP HSG 21P MK II



TE Part #1393310-2
VCFM-1000=FROM SEC

Documents

Product Drawings

250 FASTON REC 14-12 AWG TPBR

English

CAD Files

Customer View Model

ENG_CVM_CVM_41829_AN.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_41829_AN.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_41829_AN.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

Engineering Report

English

Agency Approvals

Agency Approval Document

English