



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Tab**

Wire Size: **.82 – 2.08 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Tab
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Pre-Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

	.05 in
Wire Insulation Support	With
Mating Retention Type	Locking Lance

Dimensions

Product Length	30.38 mm
Compatible Insulation Diameter Range	3.1 – 4.1 mm [.12 – .16 in]
Terminal Material Thickness	.4 mm [.015 in]
Wire Size	.82 – 2.08 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C [-40 – 230 °F]

Packaging Features

Packaging Quantity	3500
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent



chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts



TE Part # 1-1579007-4
EXTRACTION TOOL



TE Part # 4-1579007-3
EXTRACTION TOOL KIT



KIT
TE Part # 7-2150046-7
OCEAN_2.0_SPARE_PART_KIT-110F160F




TE Part # 720725-1
DAHT 250 FASTIN-ON TAB REC 18-14 ASSY



TE Part # 2150046-2
OCEAN_2.0_APPLICATOR-E-110F160F-REA

Also in the Series | FASTIN-FASTON 250



Crimp Terminal Housings(190)



Insertion & Extraction Tools(2)



Quick Disconnects(215)

Customers Also Bought





TE Part #63882-1
MAG-MATE 250 F-TAB TPBR



TE Part #927837-1
SPT REC 6.3 Contact SRC Sn



TE Part #964768-2
STD-TIM HSG SPECIAL 2P (GREY)



TE Part #CAT-M4595-T273
MCON Receptacle and Tab



TE Part #1743058-1
PL 187 REC 22-16 AWG 0.3 X 22.8 PTBR



TE Part #2232343-1
250 PL EX FLAG REC. 18-12AWG PTBR



TE Part #1SSA365212R1100
L36521211000



TE Part #3-1105050-8
HN.D-C-STI.AG.0,75

TE Part #2339924-4
.090 DIA PIN (2.3 MM) 24-20 AWG TBR

Documents

Product Drawings

FF 250 TAB 18-14 AWG PTPB

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_42098-2_DH_c-42098-2-dh.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_42098-2_DH_c-42098-2-dh.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_42098-2_DH_c-42098-2-dh.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages



1654742_HOUSEHOLD_APPLIANCES_RAST5

English

FASTIN_FASTON_Product_Line

English

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (non U.S.)

Japanese

Instruction Sheet (non U.S.)

Japanese