**Part Number :** 451460803
**Product Description :** Squba 1.8-to-Squba 1.8 Off-the-Shelf (OTS) Plug Cable Assembly, Single Row, 300.00mm, 8 Circuits, Black
**Series Number :** 45146
**Status :** Active
**Product Category :** Power and Signal Cable Assemblies



## Documents & Resources

### Drawings

451460803_sd.pdf

STEP AP242

SOLIDWORKS

Creo

## Product Environment Compliance

### Compliance

| | |
|---|---|
| GADSL/IMDS | Not Relevant |
| China RoHS | per SJ/T 11365-2006 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2024)7663-DC (21 Jan 2025) |
| EU RoHS | Compliant per EU 2015/863 |

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest
- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

---

## Part Details

### General

| | |
|---|---|
| Status | Active |
| Category | Power and Signal Cable Assemblies |
| Series | 45146 |
| Description | Squba 1.8-to-Squba 1.8 Off-the-Shelf (OTS) Plug Cable Assembly, Single Row, 300.00mm, 8 Circuits, Black |
| Application | Power, Signal, Wire-to-Wire |
| Assembly Configuration | Dual Ended Connectors |
| Connector to Connector | Squba 1.8-to-Squba 1.8 |
| Product Name | Squba |
| Type | Discrete Wire Assembly, Sealed Assembly |
| UPC | 191128910231 |

### Electrical

| | |
|---|---|
| Current - Maximum per Contact | 5.0A |
| Voltage - Maximum | 125V |

### Physical

| | |
|---|---|
| Cable Length | 300.00mm |
| Circuits (Loaded) | 8 |
| Circuits (maximum) | 8 |
| Color - Resin | Black |
| Gender | Male-Male |

| | |
|---|---|
| Lock to Mating Part | Yes |
| Material - Metal | Copper Alloy |
| Material - Plating Mating | Matte Tin |
| Material - Plating Termination | Matte Tin |
| Material - Resin | Nylon |
| Net Weight | 22.636/g |
| Number of Rows | 1 |
| Overmolded | No |
| Packaging Type | Bag |
| Pitch - Mating Interface | 1.80mm |
| Plating min - Mating | 2.500µm |
| Plating min - Termination | 2.500µm |
| Single Ended | No |
| Termination Interface Style | Crimp or Compression |
| Wire/Cable Type | UL 1061 |
| Wire Size (AWG) | 22 |

## Mates With / Use With

### Mates with Part(s)

| Description | Part Number |
|---|---|
| Squba 1.8 Sealed Single Row Receptacle Assemblies | 204220 |