**Part Number :** 475530001
**Product Description :** 1.27mm Pitch SIM Card Holder with 2 Detect Pins, 6 Circuits, Push-Push Style, Housing Height 1.80mm, without Pegs, Lead-Free
**Series Number :** 47553
**Status :** Active
**Product Category :** Memory / SIM Card Connectors



## Documents & Resources

### Drawings

475530001_sd.pdf

PK-47553-001-001.pdf

### 3D Models and Design Files

STEP AP242

SOLIDWORKS

Creo

Symbol and Footprint (Multi-Format)

### Specifications

PS-47553-001-001.pdf

## Product Environment Compliance

### Compliance

| | |
|---|---|
| GADSL/IMDS | Not Relevant |
| China RoHS | per SJ/T 11365-2006 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2025)4165-DC (25 June 2025) |
| EU RoHS | Compliant per EU 2015/863 |

Compliance Statements

- EU RoHS

- REACH SVHC
- Low-Halogen

Industry Documents
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest
- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

---

## Part Details

### General

| | |
|---|---|
| Status | Active |
| Category | Memory / SIM Card Connectors |
| Series | 47553 |
| Description | 1.27mm Pitch SIM Card Holder with 2 Detect Pins, 6 Circuits, Push-Push Style, Housing Height 1.80mm, without Pegs, Lead-Free |
| Comments | Without Pegs |
| Product Name | mini-SIM |
| Style | Push-Push |
| UPC | 822350925761 |

### Electrical

| | |
|---|---|
| Current - Maximum per Contact | 0.5A |
| Shielded | Yes |
| Voltage - Maximum | 50V DC |

### Physical

| | |
|---|---|
| Card Detection Switch | Open |
| Card Entry Location | Front |
| Circuits (Loaded) | 6 |
| Circuits (maximum) | 6 |

| | |
|---|---|
| Durability (mating cycles max) | 2500 |
| Ejector Button Side | N/A |
| Material - Contact | Copper Alloy |
| Material - Plating Mating | Gold |
| Material - Plating Termination | Gold |
| Material - Resin | High Temperature Thermoplastic |
| Material - Shell | Stainless Steel |
| Net Weight | 1.613/g |
| Packaging Type | Embossed Tape on Reel |
| PCB Locator | No |
| PCB Retention | Yes |
| Pitch - Mating Interface | 2.54mm |
| Pitch - Termination Interface | 1.27mm |
| Temperature Range - Operating | -40° to +85°C |
| Termination Interface Style | Surface Mount |

### Solder Process Data

| | |
|---|---|
| Max-Duration | 10 |
| Lead-Free Process Capability | REFLOW |
| Max-Cycle | 2 |
| Max-Temp | 250 |

## Mates With / Use With

### Mates with Part(s)

| Description | Part Number |
|---|---|
| Mates With | Standard SIM Card |