5-160446-5 ✔ ACTIVE

FASTIN-FASTON | FASTIN-FASTON 250

TE Internal #: 5-160446-5

Quick Disconnect Receptacle, Uninsulated, 17 – 13 AWG, 1.03 – 2.62 mm² Wire, 6.35 mm [.25 in] Tab Width, F-Crimp, Straight, Brass, FASTIN-FASTON 250

View on TE.com >

Terminals & Splices > Quick Disconnects







Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **1.03 – 2.62 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Locking Lance

Dimensions

Product Length	19.2 mm[.756 in]
Compatible Insulation Diameter Range	3.1 – 4.1 mm[.122 – .161 in]
Terminal Material Thickness	.41 mm[.016 in]
Wire Size	1.03 – 2.62 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Packaging Features

Packaging Quantity	5000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part

numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




TE Part # 2150235-2
OCEAN_2.0_Applicator-E-110F180F-REA




TE Part # 1-1579007-4
EXTRACTION TOOL




TE Part # 4-1579007-3
EXTRACTION TOOL KIT



TE Part # 7-2150235-7
OCEAN_2.0_SPARE_PART_KIT-110F180F



TE Part # 175040-1
FF 187 REC 0.5-1.25MM2 PTBR



TE Part # 180398-2
FF 250 REC 1-2.5MM2 TPBR



TE Part # 175042-1
FF 187 REC 2-3MM2 PTBR



TE Part # 2150235-1
OCEAN_2.0_Applicator-E-110F180F-REM



TE Part # 626328-1
FF 250 RECEPTACLE 4.0-6.0 MM2 BR




TE Part # 63467-1
FF 250 REC 14-10AWG TPBR



TE Part # 626328-2
FF 250 RECEPTACLE 4.0-6.0 MM2 TPBR

Also in the Series | FASTIN-FASTON 250



Crimp Terminal Housings(192)



Insertion & Extraction Tools(2)



Quick Disconnects(217)


Customers Also Bought

TE Part #YASX602-05SA-HE-R0
PLUG ASSY. ASX 5 WAY. DESIGN MKII.


TE Part #YASX002-05PA-HE-R0
RECEPT ASSY. ASX 5 WAY. DESIGN MKII.

TE Part #YASX102-06SE-HE-R0
RECEPT ASSY.IN-LINE.ASX 6 WAY. MKII.


TE Part #YASX602-06PE-HE-R0
PLUG ASSY. ASX 6 WAY. DESIGN MKII.




TE Part #1-282044-1
AMP MONO-SHAPE P.C.B.CONN4P. G



TE Part #925341-1
FF 250 8P HOUSING TAB POLYAMID 6.6



TE Part #1-1623797-3
SQZ10 12R 5%



TE Part #2112132-1
JPT REC 2.8 Contact SRC Blank



TE Part #2176405-4
3550 470R 5%

TE Part #8-1768016-0
CE0913W

Documents

Product Drawings

FF 250 REC 1.0-2.5MM2 TBBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5-160446-5_AP_c-5-160446-5-ap.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_5-160446-5_AP_c-5-160446-5-ap.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5-160446-5_AP_c-5-160446-5-ap.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

Application Specification

English

EB**General Application Specification for Open Barrel Terminals

English

Application Specification

English