

5-557970-3

Modular Plug, 6P/6C, unshielded, flat oval, small conductor, 6-position, category 3, 100 pcs

OBSOLETE

Replaced By:

6-557971-3 MP-66U-FS-1	Modular Plug, 6P/6C, unshielded, small conductor, standard body, flat oval, 2.29x6.61 mm cable jack OD, 100/bag
---------------------------	---

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	NETCONNECT®
Product Type	Modular plug

General Specifications

ANSI/TIA Category	3
Cable Type	Flat oval, unshielded
Conductor Type	Solid
Interface	RJ12
Positions/Loaded Contacts	6/6
Termination Type	IDC

Electrical Specifications

Insulation Resistance, minimum	500 mOhm
--------------------------------	----------

Material Specifications

Contact Base Material	Phosphor bronze
Material Type	Glass filled polycarbonate

Mechanical Specifications

Plug Insertion Life, minimum	750 times
------------------------------	-----------

Environmental Specifications

Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Flammability Rating	UL 94 V-2

Packaging and Weights

Packaging quantity	100
Packaging Type	Bag Box Carton