Circuit Board Indicators
Panel Mount Indicators
Solid State Lighting
Traffic Signals
Vehicle Lighting
Rail
Obstruction Lighting
Hazardous Area Lighting
Heliport Lighting

how to purchase
sales contacts
stock check

search
Product Line Search
Please select a Product Line to search.
Circuit Board Indicators
find

Part # / Text Search
Part No.:
Text Search:
search

quick links
Dialight Corporate Video

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. View PDF File

Application Notes
FAQs

Dialight Ltd (UK)
Dialight Garufo
Dialight BLP
LumiDrives

Circuit Board Indicators - Through Hole Indicators

P/N# **5219488F**

3 mm Lens

Description	Discrete LED Lamp
Package Options	100 pieces per bag
Product Type	Through Hole Indicators
Sub Product Type	Discrete LED
Configuration	3 mm Lens
Viewing Angle	60 degrees

Absolute Maximum Ratings (Ta = 25 °)

Solder Temp	260Â° for 6 sec
Operating Temp	-55~+100° C
Storage Temp	-55~+100° C

RoHS /pB Free
view PDF

Distributor Stock Check

Check stock with our distributors now.

5219488F

check stock

Operating Characteristics

LED Position	
Color	Green / Red
Lamp Type	Bi-Color / Bi-Color
LED Type	
Intensity Min (mcd)	3.7 / 2.5
Intensity Typ (mcd)	10.0 / 4.7
Intensity Max (mcd)	
Fwd Voltage Min	
Fwd Voltage Typ	2.1 / 2.0
Fwd Voltage Max	2.8 / 2.8
Dom Wavelength Min (nm)	
Dom Wavelength Typ (nm)	
Dom Wavelength Max (nm)	
Power Dissipation Max (mW)	
Backlighting	
Pitch Between Vertical	
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	

Copyright 2006 Dialight. All rights reserved | Privacy Policy