




Connectors > D-Shaped Connectors



Number of Positions: 9

Connector & Housing Type: **Receptacle**

Connector System: **Board-to-Board**

Connector Mounting Type: **Board Mount**

Connector Shell Size: 1

Features

Product Type Features

|                                   |                       |
|-----------------------------------|-----------------------|
| Shell Material Configuration      | Full Metal Shell      |
| Connector & Housing Type          | Receptacle            |
| Connector System                  | Board-to-Board        |
| Connector Shell Size              | 1                     |
| Connector & Contact Terminates To | Printed Circuit Board |

Configuration Features

|                       |          |
|-----------------------|----------|
| Number of Positions   | 9        |
| Number of Rows        | 2        |
| PCB Mount Orientation | Vertical |

Body Features

|                        |                  |
|------------------------|------------------|
| Insert Material        | Nylon GF, PBT GF |
| Shell Plating Material | Tin              |
| Primary Product Color  | Black            |
| Connector Profile      | Standard         |



Contact Features

|                                               |                 |
|-----------------------------------------------|-----------------|
|                                               | 30 µin          |
| Contact Underplating Material                 | Nickel          |
| Contact Mating Area Plating Material          | Gold (Au)       |
| Contact Base Material                         | Phosphor Bronze |
| PCB Contact Termination Area Plating Material | Tin             |
| Contact Shape & Form                          | Square          |
| Contact Current Rating (Max)                  | 6 A             |
| Contact Options                               | Installed       |

Termination Features

|                                          |                       |
|------------------------------------------|-----------------------|
| Termination Method to PCB                | Through Hole - Solder |
| Termination Post & Tail Length           | 10.85 mm[.427 in]     |
| Square Termination Post & Tail Dimension | .63 mm[.025 in]       |

Mechanical Attachment

|                          |               |
|--------------------------|---------------|
| Mounting Hole Diameter   | 3.05 mm       |
| Connector Mounting Type  | Board Mount   |
| PCB Mount Retention      | With          |
| PCB Mount Retention Type | Mounting Hole |
| Mating Retention         | Without       |

Housing Features

|                    |                  |
|--------------------|------------------|
| Housing Material   | Nylon GF, PBT GF |
| Shell Material     | Carbon Steel     |
| Centerline (Pitch) | 2.77 mm[.109 in] |

Dimensions

|                             |                                |
|-----------------------------|--------------------------------|
| PCB Thickness (Recommended) | 1.57 – 2.36 mm[.062 – .093 in] |
| Row-to-Row Spacing          | 2.84 mm[.112 in]               |

Usage Conditions

|                             |                            |
|-----------------------------|----------------------------|
| Operating Temperature Range | -55 – 105 °C[-67 – 221 °F] |
|-----------------------------|----------------------------|

Operation/Application

|                     |        |
|---------------------|--------|
| Shielded            | No     |
| Circuit Application | Signal |

Industry Standards



|                        |          |
|------------------------|----------|
| UL Flammability Rating | UL 94V-0 |
|------------------------|----------|

Packaging Features

|                    |      |
|--------------------|------|
| Packaging Quantity | 17   |
| Packaging Method   | Tube |

Product Compliance

For compliance documentation, visit the product page on TE.com>

|                                               |                                                                                                                                 |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                       |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                       |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                         |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2025 (250)<br>Candidate List Declared Against: JUNE 2025 (250)<br>Does not contain REACH SVHC |
| Halogen Content                               | Not Low Halogen - contains Br or Cl > 900 ppm.                                                                                  |
| Solder Process Capability                     | Wave solder capable to 265°C                                                                                                    |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # CAT-AM7-248H3  
IDC D-Sub: Plug Assembly, Wire to Wire, Signal, 2.77 mm



TE Part # 1-747944-5  
09 SHLDG ENCL PLUG, LEAD FREE



TE Part # CAT-AM7-H3  
IDC D-Sub: Plug Assembly, Low Profile, Signal, 2.77 mm



TE Part # 206509-1  
SIZE 20 KEYING PLUG



Also in the Series

AMPLIMITE HD-20

D-Shaped Connectors(285)

PCB D-Sub Connectors(285)

Customers Also Bought

TE Part #5-104069-6  
40 sys 50 hdr drra shrd sn

TE Part #2-406549-4  
IMJ,1X1,PNL GRD,LED(Y/G), S

TE Part #1761608-7  
IDC LOW PRO HDR 20P VERT SHT L

TE Part #2-1761679-9  
IDC LOW PRO HDR 26P VERT BLUE

TE Part #7-2176074-4  
CPF 0201 33K2 0.5% 50PPM 1K RL

TE Part #5103310-3  
A/L LOW PRO HDR 16P RA BLACK

TE Part #5103310-7  
A/L LOW PRO HDR 34P RA BLACK

TE Part #5227699-2  
BNC PCB VERTICAL

TE Part #5520426-4  
MJ,R/A,8P

TE Part #5536053-5  
ASSY,PIN,EUROCARD,TYPE B/2,LEA

Documents

Product Drawings

09 RCPT SP/MS STD

English

CAD Files

3D PDF

3D



Customer View Model

[ENG\\_CVM\\_CVM\\_5745183-3\\_B.2d\\_dxf.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_5745183-3\\_B.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_5745183-3\\_B.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Application Specification](#)

English

Agency Approvals

[UL Report](#)

English