




Connectors > Audio & Video Connectors > USB Connectors



USB Type: A

USB Version: 2.0

Connector Profile: **Standard**

Connector & Housing Type: **Receptacle**

Number of Ports: 1

Features

Product Type Features

USB Type	A
USB Version	2.0
Connector & Housing Type	Receptacle
Connector System	Cable-to-Board
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Mounting Legs	2
Number of Ports	1
Number of Positions	4

Body Features

Shell Plating Finish	Bright
Shell Plating Material	Tin
Connector Profile	Standard

Contact Features

--	--



Contact Underplating Material	Palladium Nickel
Contact Mating Area Plating Material Thickness	.76 μm[30 μin]
Contact Mating Area Plating Material	Gold or Gold Flash
Contact Current Rating (Max)	1 A

Termination Features

Termination Post & Tail Length	2.84 mm[.112 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Locking Feature	With
PCB Mount Location	Top Mount
PCB Connector Seating	Flush
PCB Mount Retention Type	Straight Leg
Panel Mount Feature Type	Flange
Connector Mounting Type	Board Mount

Housing Features

Housing Color	Natural
Housing Material	Thermoplastic
Body Orientation	Right Angle
Centerline (Pitch)	2 mm, 2.5 mm[.078 in][.098 in]

Dimensions

PCB Thickness (Recommended)	1.57 mm[.062 in]
-----------------------------	------------------

Usage Conditions

Soldering Temperature (Max)	260 °C[500 °F]
Mating Cycles (Max)	1500
Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]

Operation/Application

Halogen Free	No
Circuit Application	Power & Signal

Industry Standards

Moisture Sensitivity Level	1
Test Identification (TID)	60000279
UL Flammability Rating	UL 94V-0



Packaging Features

Packaging Quantity	1920
Packaging Method	Box, Box & Tube

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1487593-1
USB, A-BLUNT,28/24,WHT,2.0M



TE Part # 1487600-1
USB, A-BLUNT,28/26,BLK,1.0M



TE Part # 1734028-1
Std USB Type A, Plug, Natural




TE Part # 1-1734028-1
Std USB, Type A, Plug, Natural



TE Part # 1487593-2
USB, A-BLUNT,28/24,WHT,1.5M




TE Part # 1-1734028-3
Std USB, Type A, Plug




TE Part # 1496476-1
STD USB-A TO MINI-B ASSY, 1M



TE Part # 1487599-1
USB, A-BLUNT,28/28,BLK,0.83M



TE Part # 2142872-1
cable assy, usb a plug to 5p hsg



TE Part # 1929690-1
USB CABLE, USB A to Mini USB,Blue




TE Part # 1827525-1
MECHATROLINK II CONNECTOR KIT


Customers Also Bought



TE Part #3826043001
44A1121-20-0/2-9



TE Part #281786-5
PLUG HE14 IDC 180 5 P AWG 28-26




TE Part #3-1123722-3
3.96 EP PLUG HSG 3P(BLUE)



TE Part #2-1614354-3
RN 0603 59R 0.1% 10PPM CUT LENGTH



TE Part #1676402-2
RN 0805 64K9 0.1% 10PPM 1KRL




TE Part #1761607-6
IDC LOW PRO HDR 16P RA LAT BLK



TE Part #1-1954289-1
Connector,Blade & Recpt 2 Pos



TE Part #6-2176231-3
3522 3K9 1% 3W



TE Part #5-2349820-3
PCIEG4,SMT,V,98P,30u,ML,HT,OEWS



TE Part #1-5499141-1
A/L UNIV HDR 60P RA LAT

Documents



Product Drawings

Std USB Type A, R/A, T/H, Natural

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_6364372-2_O.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_6364372-2_O.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6364372-2_O.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English