6368035-3 ✔ ACTIVE

AMP-METRIMATE

TE Internal #: 6368035-3

RJ45 Connector, Multiple Ports, 2 x 6, Jack, Shielded, Cat 5, Standard - Latch Down, 8 Position, Offset - Overhangs PCB Profile, AMP-METRIMATE

View on TE.com >

Connectors > Modular Jacks & Plugs > RJ45 Connectors



Modular Jack & Plug Interface Type: **RJ45**

Port Configuration: **Multiple Ports**

Port Matrix Configuration: **2 x 6**

Modular Jacks & Plugs Products: **RJ Type Jacks & Plugs**

Connector Contact Density: **Standard**

Features

Product Type Features

Connector Product Type	Connector Assembly
Modular Jack & Plug Interface Type	RJ45
Modular Jacks & Plugs Products	RJ Type Jacks & Plugs
Modular Connector Style	Jack
Grounding Options	PCB and Panel Ground
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of PCB Ground Tabs	9
Multiple Port Configuration	Stacked
Port Configuration	Multiple Ports
Port Matrix Configuration	2 x 6
Connector Contact Density	Standard
Number of Positions	8
Number of Loaded Positions	8
PCB Mount Orientation	Right Angle

Body Features

LED Color (Bottom Left)	Green/Yellow
LED Color (Bottom Right)	Green/Yellow

Grounding Tab Plating Material	Tin over Copper
Shield Plating Material	Tin over Copper
Shield Material	Copper Alloy
LED Color (Top Right)	Green/Yellow
LED Color (Top Left)	Green/Yellow
Modular Jack Latch Orientation	Standard - Latch Down
Connector Profile	Offset - Overhangs PCB

Contact Features

Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material	Gold (Au)
Contact Base Material	Phosphor Bronze
Contact Mating Area Plating Material Thickness	1.27 µm[50 µin]

Termination Features

Termination Method to PCB	Through Hole - Press-Fit
Termination Post & Tail Length	4.35 mm[.171 in]

Mechanical Attachment

Panel Mount Feature	Without
Connector Mounting Type	Board Mount, Panel Mount

Housing Features

Mating Entry Location	Side
Centerline (Pitch)	1.02 mm[.04 in]
Housing Color	Black
Housing Material	PBT Polyester

Dimensions

PCB Thickness (Recommended)	1.57 mm[.062 in]
Connector Height	22.99 mm[.905 in]

Usage Conditions

Operating Temperature Range	-30 – 70 °C[-22 – 158 °F]

Operation/Application

Indicator Type	LED
Shielded	Yes

Circuit Application	Signal

Industry Standards

UL Flammability Rating	UL 94V-0
Performance Category	Cat 5

Packaging Features

Packaging Quantity	10
Packaging Method	Tray

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Out of Scope
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts

TE Part # 1521003-2
CAT 5E CABLE ASSY, 8 POS RJ45




TE Part # 188729-1
8P.COVER/SOLD.STOP


Also in the Series | AMP-METRIMATE




Board-to-Board Headers & Receptacles(1)



Card Edge Power Connectors(1)



Connector Hardware(1)




PCB Headers & Receptacles(1)




Rack & Panel Connectors(1)



Rectangular Power Connectors(3)



RJ45 Connectors(39)



Standard Rectangular Connectors(2)

Customers Also Bought



TE Part #178877-1
SCREWLOCK WITH SPRING WASHER



TE Part #1888653-4
2X1 OFFSET ST/JK WITH LEDS



TE Part #1-1939995-0
DYNAMIC D1100D SMT-HDR V 40P BLACK X



TE Part #2007705-1
IMP100S,R,RA3P10C,UG,39



TE Part #2007788-3
IMP100S,H,V3P10C,UG,OEW39,5.5




TE Part #2-2013289-3
EMBOSS TAPE DDR3 204P 5.2H STD Au 0.76



TE Part #2042088-2
Vert.Male, IEC L2



TE Part #5100147-1
Z-PACK/A RAF 110P



TE Part #5536649-1
2MM FB,ASY,010,PWR,REC,EN,SEQ

TE Part #4-406549-8
IMJ,1X1,PNL GRD,LED(YG/YG), SN

Documents

Product Drawings

2X6 OFFSET STK MJ,SHLD,G/YLED

English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_6368035-3_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_6368035-3_A.3d_igs.zip

English

Customer View Model

ENG_CVM_6368035-3_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

Application Specification

English

Application Specification

English

Agency Approvals

UL Report

English