



Part Number : [733870021](#)
Product Description : Precision Test Connector,
2.4mm PCB Jack Receptacle, 2-Hole Flange Mount,
Solderless Compression Contact, with 2 Screws
6.35mm, PCB Thickness 1.96-3.99mm, 50 Ohms
Series Number : 73387
Status : Active
Product Category : RF / Coaxial Connectors



Documents & Resources

Drawings

[733870021 sd.pdf](#)
[Symbol and Footprint \(Multi-Format\)](#)

Specifications

[AS-89675-446-001.pdf](#)
[PS-89675-0410-001.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	 per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Contains Lead per D(2025)4165-DC (25 June 2025)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

Part Details

General

Status	Active
Category	RF / Coaxial Connectors
Series	73387
Description	Precision Test Connector, 2.4mm PCB Jack Receptacle, 2-Hole Flange Mount, Solderless Compression Contact, with 2 Screws 6.35mm, PCB Thickness 1.96-3.99mm, 50 Ohms
Application	RF
Comments	Solderless Compression
Product Name	Precision Test - 2.4mm
Style	PCB
Type	Subminiature
UPC	884982517653

Electrical

Frequency	50 GHz
Impedance	50Ω
Power / Voltage	VOLTAGE: 500 Vrms@Sea Level

Physical

Cable Attachment	N/A
Gender	Jack
Keying to Mating Part	N/A

Net Weight	2.115/g
Orientation	Straight
Packaging Type	Tray
Panel Mount	No
Panel Mount Method	N/A
PCB Mounting	Surface Mount - Compression
PCB Thickness - Recommended	4.64mm
Reverse Polar	No
Wire/Cable Type	N/A

Solder Process Data

Lead-Free Process Capability	N/A
------------------------------	-----