




**Part Number :** [878321423](#)

**Product Description :** 2.00mm Pitch, Milli-Grid PCB Header, Dual Row, Vertical, Surface Mount, Shrouded, Lead-Free, 14 Circuits, 0.76µm Gold (Au) Plating, with Pick-and-Place Cap, with Locking Windows and Center Polarization Slot, with PCB Locator, Tube

**Series Number :** 87832

**Status :** Active

**Product Category :** PCB Headers and Receptacles



## Documents & Resources

### Drawings

[878321423 sd.pdf](#)

[PK-87831-001-001.pdf](#)

### 3D Models and Design Files

[STEP AP242](#)

[SOLIDWORKS](#)

[Creo](#)

[Symbol and Footprint \(Multi-Format\)](#)

### Specifications

[503940001-AS-000.pdf](#)

[PS-87831-027-001.pdf](#)

[878320001-TS-000.pdf](#)

## Product Environment Compliance

### Compliance

|                    |                                                                                                           |
|--------------------|-----------------------------------------------------------------------------------------------------------|
| GADSL/IMDS         | Compliant with Exemption 44; 34; 33                                                                       |
| China RoHS         |  per SJ/T 11365-2006 |
| EU ELV             | Not Relevant                                                                                              |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-21                                                                        |

|            |                                                    |
|------------|----------------------------------------------------|
| REACH SVHC | Not Contained per D(2025)4165-DC<br>(25 June 2025) |
| EU RoHS    | Compliant per EU 2015/863                          |

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

---

**Part Details**

**General**

|                |                                                                                                                                                                                                                                        |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Status         | Active                                                                                                                                                                                                                                 |
| Category       | PCB Headers and Receptacles                                                                                                                                                                                                            |
| Series         | 87832                                                                                                                                                                                                                                  |
| Description    | 2.00mm Pitch, Milli-Grid PCB Header, Dual Row, Vertical, Surface Mount, Shrouded, Lead-Free, 14 Circuits, 0.76µm Gold (Au) Plating, with Pick-and-Place Cap, with Locking Windows and Center Polarization Slot, with PCB Locator, Tube |
| Application    | Signal, Wire-to-Board                                                                                                                                                                                                                  |
| Comments       | With Cap, Contact Molex for application in automotive industry                                                                                                                                                                         |
| Component Type | PCB Header                                                                                                                                                                                                                             |
| Product Name   | Milli-Grid                                                                                                                                                                                                                             |
| UPC            | 822348352142                                                                                                                                                                                                                           |

## Agency

|     |         |
|-----|---------|
| CSA | LR19980 |
| UL  | E29179  |

## Electrical

|                               |      |
|-------------------------------|------|
| Current - Maximum per Contact | 2.0A |
| Voltage - Maximum             | 125V |

## Physical

|                                |                 |
|--------------------------------|-----------------|
| Breakaway                      | No              |
| Circuits (Loaded)              | 14              |
| Circuits (maximum)             | 14              |
| Color - Resin                  | Black           |
| Durability (mating cycles max) | 100             |
| First Mate / Last Break        | No              |
| Flammability                   | 94V-0           |
| Glow-Wire Capable              | No              |
| Guide to Mating Part           | No              |
| Keying to Mating Part          | Yes             |
| Lock to Mating Part            | Yes             |
| Material - Metal               | Phosphor Bronze |
| Material - Plating Mating      | Gold            |
| Material - Plating Termination | Tin             |
| Material - Resin               | Nylon           |
| Net Weight                     | 0.671/g         |
| Number of Rows                 | 2               |
| Orientation                    | Vertical        |
| Packaging Type                 | Tube            |
| PCB Locator                    | Yes             |
| PCB Retention                  | None            |
| Pitch - Mating Interface       | 2.00mm          |
| Pitch - Termination Interface  | 2.00mm          |
| Plating min - Mating           | 0.762µm         |
| Plating min - Termination      | 1.880µm         |
| Polarized to PCB               | No              |

|                               |                    |
|-------------------------------|--------------------|
| Robotic Placement             | Pick and Place Cap |
| Shrouded                      | Fully              |
| Stackable                     | No                 |
| Temperature Range - Operating | -55° to +105°C     |
| Termination Interface Style   | Surface Mount      |

### Solder Process Data

|                              |        |
|------------------------------|--------|
| Max-Duration                 | 10     |
| Lead-Free Process Capability | REFLOW |
| Max-Cycle                    | 1      |
| Max-Temp                     | 260    |

---

### Mates With / Use With

#### Mates with Part(s)

| Description                                               | Part Number  |
|-----------------------------------------------------------|--------------|
| Milli-Grid Dual Row Receptacle Housings                   | <u>51110</u> |
| Milli-Grid Vertical Through Hole PCB Receptacles          | <u>78787</u> |
| Milli-Grid Top Entry Surface Mount PCB Receptacles        | <u>78788</u> |
| Milli-Grid Vertical Through Hole PCB Receptacles          | <u>79107</u> |
| Milli-Grid Vertical Through Hole PCB Receptacles          | <u>79108</u> |
| Milli-Grid Top/Bottom Entry Surface Mount PCB Receptacles | <u>79109</u> |
| Milli-Grid Dual Row Cable-to-Board Receptacles            | <u>87568</u> |