969599-1 ✔ ACTIVE

MQS


TE Internal #: 969599-1

Horizontal, Wire-to-Board, 32 Position, 2 Row, 2.54mm [.1in] Centerline, Gold (Au), Printed Circuit Board, 7.5A Contact Current Rating (Max), Signal

View on TE.com >

Automotive Parts > Automotive Connectors > Automotive Headers > Signal Header




PCB Mount Orientation: **Horizontal**

Contact Current Rating (Max): **7.5 A**

Termination Method to PCB: **Through Hole - Solder**

Sealable: **No**

Centerline (Pitch): **2.54 mm [.1 in]**

All Signal Header (232)

Features

Product Type Features

Connector Product Type	Connector Assembly
Mixed & Hybrid Header	No
Header Type	Fully Shrouded
Connector Shape	Rectangular
Sealable	No
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Signal Positions	32
Number of Sections	1
PCB Mount Orientation	Horizontal
Number of Positions	32
Number of Rows	2

Electrical Characteristics

Nominal Voltage Architecture	12 V

Body Features

Connector & Keying Code	B, D, E
Primary Product Color	Black

Contact Features

Mating Tab Width	.63 mm[.025 in]
Mating Tab Thickness	.63 mm[.025 in]
Contact Type	Tab
Contact Current Rating (Max)	7.5 A
Contact Mating Area Plating Material	Gold (Au)

Termination Features

Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Panel Mount Feature	With
PCB Mount Retention	With
Mounting Holes	With
PCB Mount Retention Type	Mounting Hole
Mating Alignment	With
PCB Mount Alignment	Without
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	2.54 mm[.1 in]

Dimensions

Connector Width	28.4 mm[1.11 in]
PCB Thickness (Recommended)	2 mm[.078 in]
Profile Height from PCB	17 mm[.669 in]
Connector Length	55.8 mm[2.19 in]

Usage Conditions

Operating Temperature (Max)	120 °C[248 °F]
Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]

Operation/Application

Solder Process	Wave Solder Capable
Shielded	No
Circuit Application	Signal

Packaging Features

Packaging Quantity	256
Packaging Method	Tray

Other

Interface Number	1719059-1

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 240°C

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 1719059-1
32POS MQS REC

Customers Also Bought



TE Part #6767153004
FLDWC0311-0.50-0



TE Part #1-179277-5
DYNAMIC 3200 HDR ASSY 4P H



TE Part #1-929278-2
MQS STIFT M.A-PIN




TE Part #7-967570-4
2POS MQS TAB SEALED COD A



TE Part #2208165-1
20POS,NANO MQS,HEADER ASSY, CODA



TE Part #2315405-1
4POS,TAB0.5X0.4,HDR ASSY,90DEG, COD A



TE Part #5749721-7
68 50SR VERT RCPT ASSY

TE Part #6-1768709-1
LBG-U-02797



TE Part #CAT-SIGH262
Signal Header

Documents

Product Drawings

32pos MQS .63 header 90deg

English

32pos MQS .63 header 90deg

English

CAD Files

Customer View Model

ENG_CVM_CVM_969599-1_B.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_969599-1_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_969599-1_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

Product Specification

English