# HVAC Disconnects
## Fused and Non-Fused

# Series B22__



Metallic
Fused Disconnect



Metallic
Non-Fused Disconnect



Non-Metallic Disconnect

**RAINPROOF AIR CONDITIONER PULLOUT UNITS**
**Fused and Non-Fused Features:**

- NEMA 3R Rainproof.
- Compact design but offers ample working space.
- Internal shield can be removed without tools.
- Specifications are embossed on internal shield.
- Knockouts on back, bottom, and both sides.
- Touchproof construction.
- Padlockable
- Agency Approvals:
  UL Listed to UL 1429
  CUL Certified

## METALLIC

Single Phase 2W, 240 Volts AC
UL Guide WGEW
Wire Range: #14 - #2 awg, Al-Cu wire

| Main Rating | Catalog Number | | Maximum HP[1] 120V | 240V | Apprx. Dimensions H x W x D(in.) |
|---|---|---|---|---|---|
| 30A** | B221-30F* | (Fused) | 2 | 3 | 7-5/8 x 6-1/4 x 3-5/8 |
| 60A** | B222-60F* | (Fused) | 3 | 10 | 7-5/8 x 6-1/4 x 3-5/8 |
| 60A*** | B222-60NF | (Non-fused) | 3 | 10 | 8-5/8 x 4-7/8 x 3-5/8 |
| - | 96-3258-4 | Replacement Pullout Head | | | |

**Suitable for use as service equipment with optional field installed lug kit Number DPFG*

Shipping Weight - 2.7 lbs. per unit.

Case pack quantity 10, Case pack weight 30 lbs.
Carton Dimensions:
**14-1/2" L x 11-1/2" W x 9-1/2" H; ***14-3/4" L x 11-1/2" W x 9-1/2" H

## NON-METALLIC

Single Phase 2W, 240 Volts AC
UL Guide WGEW
Material: Norell
Flammability Rating: 94 V-O
Wire Range: #14 - #2 awg, Al-Cu wire

| Main Rating | Catalog Number | | Maximum HP[1] 120V | 240V | Apprx. Dimensions H x W x D (in.) |
|---|---|---|---|---|---|
| 30A | B221-30FNM | (Fused) | 2 | 3 | 8-5/8 x 5 x 3-1/2 |
| 60A | B222-60FNM | (Fused) | 3 | 10 | 8-5/8 x 5 x 3-1/2 |
| 60A | B222-60NFNM | (Non-Fused) | 3 | 10 | 8-5/8 x 5 x 3-1/2 |

Shipping Weight - 1.5 lbs. per unit.
Case pack quantity 10, Case pack weight 16 lbs.
Carton Dimensions: 21-3/8" L x 12-1/2" W x 10-1/2" H

[1] Rated with Bussmann LPN-RK, FRN-R, DLN-R and HAC-R Dual Element Time Delay Fuses.

The only controlled copy of this BIF document is the electronic read-only version located on the Bussmann Network Drive. All other copies of this BIF document are by difinition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.