

1550 Standard & 1350 High Inrush Switches 150A to EN61058-1 and 16A 250Vac



- ▶ Standard rocker switch
- ▶ 1350/53 high inrush
- ▶ Choice of switching circuits including 3 position
- ▶ Push-on, solder and PCB terminals
- ▶ Choice of bezel styles
- ▶ Choice of panel cut outs
- ▶ Matching indicator
- ▶ Double pole
- ▶ Splashproof option
- ▶ Bezel size 'A' style 30.2 x 25.0



In house test



In house test



1550 Series 16(4)A 250Vac T125

UL CSA 16A 250Vac, (2 posn) 250Vac 1hp, 125Vac 1/2hp, (3 posn) 250 Vac 1/2hp, 125Vac 1/4hp.
UL 85°C, file E45221, CSA file LR10990.

20A 28Vdc.

1350 series 16(4)A 250Vac T85 1E4 (10,000 Ops.)
On request 16(6)A 250Vac T125 5E4 (50,000 Ops.)
150A Inrush to EN61058-1.

UL CSA 20A 250Vac 1hp, 125Vac 1/2hp.
UL 72Vdc 7A, 36Vdc 14A.
UL 85°C, file E45221, CSA file LR10990.

20A 28Vdc

RoHS compliant

3mm contact gap except if marked µ.
Technical data on pages 4 & 5 (switches), 66 (indicators).

C 1553 A L ---
TERMINAL FUNCTION ROCKER BODY PRINT, COLOUR, VOLTAGE ETC

TERMINAL	FUNCTION			ROCKER
C 6.3 x 0.8	Approvals & ratings vary with function ON OFF Switches - ON when pressed over terminal 1			
H 4.8 x 0.8*	Standard 1550	High Inrush 1350	ON - OFF 	A Softline Matt Lit (not momentary)
K 2.8 x 0.8*	1551 HP rating N/A		ON - OFF (momentary ON) 	B Splashproof Softline Matt or gloss Gloss only Lit (not momentary)
T Solder	1552 HP rating N/A		ON - OFF (momentary OFF) 	V Curved Matt or gloss Gloss only Lit (not momentary)
U Right angle T Solder (Not DP)	1553 Not W, X or B rocker	1353 Not W, X or B rocker	ON - OFF Lit 	W Splashproof Curved
X PCB 0.8Sq*	1560 µ		ON - ON 	P Lit window Matt Lit (not momentary)
	1561 µ HP rating N/A		ON - ON (momentary 1 side) 	X Two colour Matt
	1562 µ In house tests only		2 Circuit ON - ON 	F Flat lens Gloss (0480 only) (ON OFF only - not momentary) Top view
	1570 µ 125V & 250V 1/2 HP H terminal rated T100 only		ON - OFF - ON 	A Softline lens Matt (0480 only) as F but with raised profile
	1571 µ HP rating N/A H terminal rated T100 only		ON - OFF - ON (momentary 1 side) 	R Round
	1572 µ HP rating N/A H terminal rated T100 only		ON - OFF - ON (momentary 2 sides) 	
	1484 µ In-house tested to 10(3)A 250Vac (B rocker only)		3 position selective OFF - A - A+B 	
	1487 µ In-house tested to 10(3)A 250Vac (B rocker only)		3 position selective A - B - C (link not supplied) 	
	0480 X terminal N/A		Indicator Technical data on page 66 	



C1350AL ---



C1550XL ---



C1553PL ---



C1553RA ---
Shown with M614 bezel cover



C0480AL ---



Optional snap-in M441 barrier









C1553AA with additional
M616 guard
Cut-out 22.0/22.1 x 29.4/29.5
Guard accepts "A" body only



C0480RA ---

BODY

Panel cut-out * Bezel
Cut-outs must be punched in the direction of insertion



OPTIONS

Finish Matt is standard.

Colour Call factory for custom colours.
A full range is available for large orders.

Legend printing Select from the examples or
call factory for custom legends.

Lamp voltage Call factory for details.

Blanking plates A0494 Dummy units
to fill unused panel holes.


Protective cover (designed to IP65)
Snaps on to A, L, Q or T bodies (add G after body
in cat no), this reduces maximum acceptable
panel thickness to 1.2mm.



Panel sealing washer W42 is available for the
above body sizes, this reduces maximum
acceptable panel thickness to 2mm. Covers are
not suitable for momentary types.

For all options call the factory.

DIMENSIONS (mm)



Terminal spacing - Poles 10.2 between centres


Panel thickness

A,Q	0.75 to 3.3mm
L,B,T	0.75 to 2.5mm
R	0.75 to 3.0mm

* For cut-out details on
momentary switches call the
factory.

1350 High inrush, positive break switching

The 1350 series mechanism ensures
contact welds formed at switch-on,
are positively separated by the
plunger tube acting directly on the
step in the moving contact.



Examples of printing



EN602A



EN730



EN822