
CUI Devices is now Same Sky! Learn More

SERIES: C14 | DESCRIPTION: PANEL MOUNT ENCODER

FEATURES

- 2-bit quadrature output
- compact
- rugged metal design
- 1 million cycle life
- multiple termination options
- IP65 rating option
- plastic shaft options available for medical applications



ELECTRICAL

parameter	conditions/description	min	typ	max	units
power supply	3.3Vdc input models 5Vdc input models	3.168 4.75	3.3 5	3.432 5.25	Vdc Vdc
supply current	3.3Vdc input models 5Vdc input models			40 20	mA mA
output	open collector				
output code	2-bit quadrature, channel A leads channel B by 90° with clockwise rotation				
power consumption	3.3Vdc input models 5Vdc input models			132 100	mW mW
output resolution	4 ppr (16 cpr), 8 ppr (32 cpr)				
angle of throw	16 detent postion models 32 detent postion models		22.5 11.25		° °

PUSH SWITCH SPECIFICATIONS

parameter	conditions/description	min	typ	max	units
rating	12 Vdc at 50 mA				
contact resistance				200	mΩ
isolation voltage	for 1 minute		250		Vac
insulation resistance		100			MΩ
operating push force		3.5	4.5	5.5	N
travel		0.2	0.5	0.8	mm
bounce				10	ms
push switch life			1,000,000		cycles

ENVIRONMENTAL

parameter	conditions/description	min	typ	max	units
operating temperature		-10		70	°C
storage temperature		-20		80	°C
vibration	10~55Hz with a peak to peak amplitude of 1.5mm				
shock	half sine wave for 11ms		50		G
cold test	at -20°C for 96 hours				
heat test	at +80°C for 96 hours				


ENVIRONMENTAL (CONTINUED)

parameter	conditions/description	min	typ	max	units
temperature change test	at -10~70°C for 30 minutes each				
humidity test	at 40°C, 90~95% humidity for 96 hours				
RoHS	yes				

MECHANICAL

parameter	conditions/description	min	typ	max	units
shaft load	radial axial			10 15	N N
operational torque	without detent with detent	 0.2	 0.4	0.2 0.6	N·cm N·cm
mounting torque			100		N·cm
rotational life			1,000,000		cycles
weight			11		g

OUTPUT WAVEFORMS



*The code repeats from 1 to 4.

Position / Output	1	2	3	4	5
A	0	1	1	0	0
B	0	0	1	1	0

(1) 3.3V : "0" : 0.8V max. "1" : 2.3V min.

(2) 5V : "0" : 1.0V max. "1" : 3.0V min.


PART NUMBER KEY

C14 X XX X - X X X X

- **C14** — Base Number
- **X** — Detent:
  D = with detent
  N = without detent
- **XX** — Angle of throw:
  16 = 22.5° for code change and 16 detent positions
  32 = 11.25° for code change and 32 detent positions
- **X** — Push Switch:
  P = with push switch
  N = without push switch
- **X** — Termination:
  A = Ø0.5 mm holes
  B = 130 mm cable with connector
  C = with header I
  D = with header II
  E = horizontal PCB
  F = vertical PCB
- **X** — Shaft Diameter:
  1 = Ø3.175 mm (1/8")
  2 = Ø6 mm
  2P = Ø6 mm, plastic
  3 = Ø6.35 mm (1/4")
  3P = Ø6.35 mm (1/4"), plastic
- **X** — Waterproof:
  "blank" = standard
  A = IP65
- **X** — Input Voltage:
  "blank" = 5 V input
  3 = 3.3 V input


OUTPUT CIRCUIT

5V Input



＊R2, R3:External pull-up resistors 5.1KΩ

3.3V Input




＊R3, R4:External pull-up resistors 5.1KΩ

MECHANICAL DRAWING

5V INPUT, WITH PUSH SWITCH


units: mm



MECHANICAL DRAWING (CONTINUED)


5V INPUT, WITHOUT PUSH SWITCH

units: mm



3.3V INPUT, WITH PUSH SWITCH


units: mm



MECHANICAL DRAWING (CONTINUED)

3.3V INPUT, WITHOUT PUSH SWITCH


units: mm




MECHANICAL DRAWING, TERMINATION OPTIONS

units: mm


OPTION A: Ø0.5MM HOLES




OPTION B: 130MM CABLE WITH CONNECTOR



OPTION C: HEADER I




OPTION D: HEADER II




MECHANICAL DRAWING, TERMINATION OPTIONS (CONTINUED)

units: mm


OPTION E: HORIZONTAL PCB




PCB Layout
tolerance: ±0.05




OPTION F: VERTICAL PCB



PCB Layout
tolerance: ±0.05



WATERPROOF MOUNTING



No.	Qty.	Component
1	1	waterproof washer
2	1	panel
3	1	toothed lock washer
4	1	nut

Note: 1. Protects against ingress of water (IP65) from front side of panel only.

REVISION HISTORY

rev.	description	date
1.0	initial release	02/25/2009
1.01	applied new spec template, updated operating temperature, updated 3.3V PCB	05/20/2014
1.02	brand update	10/04/2019
1.03	added plastic shaft models	10/14/2020
1.04	logo, datasheet style update	08/05/2022
1.05	CUI Devices rebranded to Same Sky	09/12/2024

The revision history provided is for informational purposes only and is believed to be accurate.

same sky

Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

sameskydevices.com