



Terminals & Splices > Splices



Wire Size: .382 – .963 mm²

Sealable: **Yes**

Splice Features: **Splice Kit**

Compatible Insulation Diameter Range: **2.79 mm [.11 in]**

Features

Product Type Features

Splice Accessory Type	Splice
Sealable	Yes
Wire Insulation Support Retention Type	Non-Insulation Support

Configuration Features

Number of Serrations	0
Compatible With Wire & Cable Type	Discrete Wire

Body Features

Insulation Material	Modified Polyvinylidene
Splice Features	Splice Kit

Contact Features

Contact Base Material	Copper Alloy
Barrel Type	Closed

Dimensions

Wire Size	754 – 1900 CMA
Compatible Insulation Diameter Range	2.79 mm[.11 in]
Barrel Inside Diameter	1.55 mm[.061 in]
Product Length	29.2 mm[1.15 in]

Usage Conditions

--	--



Insulation Option	Fully Insulated
Operating Temperature Range	-55 – 150 °C[-67 – 302 °F]

Industry Standards

Government Qualified Splice	No
-----------------------------	----

Packaging Features

Packaging Method	Bag/Box
------------------	---------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



Customers Also Bought

TE Part #0063733001
55A1122-28-0/2-9

TE Part #5-104363-8
09 MTE HDR SRST LATCH .100CL

TE Part #5-104894-2
20 50/50 GRID RA HDR LF

TE Part #130524
BRAZED 22-16 SPADE #4

TE Part #4-640426-8
18P MTA156 CONN ASSY 18AWG
ORA

TE Part #787317-4
40 BMATE RCPT ASSY, PB FREE

TE Part #9-1617756-7
FCAC-325-AY4

TE Part #8-1879337-7
CPF 0603 19K6 1% 50PPM 1K RL

TE Part #9-1879338-0
CPF 0603 226K 1% 50PPM 1K RL

TE Part #2825261-4
4P VAL-U-LOK HCS VRT HDR W/P V0

Documents

Product Drawings

D-436-0147

English

Datasheets & Catalog Pages

1654025_Sec8_D-436

English

Harness Repair Products Quick Reference Guide

English

6-1195312-4

22 – 18 AWG, .382 – .963 mm² Wire, 754 – 1900 CMA, Fully Insulated, Sealable, Splice Kit, Copper Alloy, 0 Serration, 29.2 mm [1.15 in] Length, Bag/Box

