

COUPLER

EASY PB Coupler | Coupler for light management systems




Product features

- Pushbutton coupler for connection to EASY control units
- 8 inputs for floating make contacts
- Group and scene control, central switching and dimming, sequencer start/stop
- Floating contacts of motion sensors or timer switches can be connected
- Up to 2 EASY pushbutton couplers can be connected to the overall system

Technical data

Dimensions & weight



Length	47.0 mm
Width	44.0 mm
Height	13.0 mm
Product weight	41.00 g

Temperatures

Ambient temperature range	0...+50 °C
---------------------------	------------

Capabilities

Dimming interface	EASY
Type of installation	Integrated in flush device box

Certificates & standards

Type of protection	IP20
--------------------	------

Equipment / Accessories

- Connection via Y-connector for multiple control units (included)

Download Data

File	
	Declarations of conformity Declaration of conformity Sensor Kit LMS CI Box
	Installation/Operation notice EASY PB Coupler Technical instructions
	Installation guide EASY PB Coupler Technical instructions

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321915597	COUPLER	Shipping carton box 25	340 mm x 174 mm x 160 mm	9.47 dm ³	2760.75 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.