HDP24-24-14SE ✔ ACTIVE


DEUTSCH | DEUTSCH HDP, DEUTSCH HD

TE Internal #: HDP24-24-14SE

12 V / 24 V / 48 V, 14 Position, Automotive Housing for Female Terminals, Wire-to-Wire, Sealable, Black, Wire & Cable, Power, Panel Mount, Hybrid

View on TE.com >

Automotive Parts > Automotive Connectors > Automotive Housings > DEUTSCH HDP20 Housings



Nominal Voltage Architecture: **12 V, 24 V, 48 V**

Connector & Housing Type: **Housing for Female Terminals**

Number of Positions: **14**

Sealable: **Yes**

Operating Temperature Range: **-55 – 125 °C [-67 – 257 °F]**

All DEUTSCH HDP20 Housings (357)

Features

Product Type Features

Mixed & Hybrid Connector	Yes
Connector Shape	Circular
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Primary Locking Feature	Integrated in Housing
Connector System	Wire-to-Wire
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Blank Cavity Position	0
Connector Seal Code	E Seal
Number of Positions	14

Electrical Characteristics

Operating Voltage	250 VDC
Nominal Voltage Architecture	12 V, 24 V, 48 V

Body Features

Cable Exit Angle	180 °
Primary Product Color	Black

Contact Features

Contact Size	Size 12, Size 16, Size 4
Contact Type	Socket
Mating Pin Diameter	1.59 mm, 2.39 mm, 5.72 mm[.063 in][.094 in][.225 in]
Contact Current Rating (Max)	13 A, 25 A, 100 A

Mechanical Attachment

Strain Relief	Add By Accessory
Terminal Position Assurance	No
Mating Alignment Type	Guide Post
Mating Alignment	With
Connector Mounting Type	Panel Mount

Housing Features

Housing Material	PA GF

Dimensions

Compatible Insulation Diameter Range	1.35 – 3.05 mm, 2.46 – 4.01 mm, 6.63 – 7.42 mm[.053 – .12 in][.097 – .158 in][.261 – .292 in]
Product Width	50.8 mm[2 in]
Product Length	41.86 mm[1.648 in]
Connector Height	47.63 mm[1.875 in]

Usage Conditions

Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operating Temperature (Max)	125 °C[257 °F]

Operation/Application

Circuit Application	Power

Industry Standards

IP Rating	IP67
UL Flammability Rating	20mm Flame Test per Standard UL-94

Packaging Features

Packaging Method	Box

Other

Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: FEB 2026 (253) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # CAT-H396-CH8172
DEUTSCH HDP20 Housings



TE Part # 0411-336-1605
EXT TOOL, SIZE 16, 16-20 AWG, E, DRK BLU



TE Part # 0411-337-1205
EXT TOOL, SIZE 12, 12-14 AWG, E, ORG



TE Part # CAT-D48-SP729
DEUTSCH Sealing Plugs



TE Part # 0411-204-1605
EXT TOOL, SIZE 16, 16-18 AWG, N, DRK BLU



TE Part # CAT-H396-M8649
Lockwashers and Panel Nuts for Deutsch HDP20

TE Part # 62036-40
62036 HDP24 FLANGE-SEAL silicone 60shore



TE Part # HD30-24BT-90-BK
BOOT, 24SZ, RA, BLK

TE Part # HD30-24BT
BOOT, 24SZ, ST, GRY

TE Part # 114009-ZZ
EXT TOOL, SIZE 4, 6 AWG, N, WHT

TE Part # 16-04477
GASKET, 24SZ, BLK, HD30

TE Part # CAT-H396-RC8382
Receptacle Protective Caps — DEUTSCH HDP20



TE Part # HD30-24BT-BK
BOOT, 24SZ, ST, BLK



TE Part # 24-D-PUNCH
D-HOLE PUNCH, SIZE 24

Also in the Series | DEUTSCH HDP

Automotive Housings(636)

Automotive Seals & Cavity Plugs(10)

Connector Seals & Cavity Plugs(10)

Other Automotive Connector Accessories(17)


Also in the Series | DEUTSCH HD



Automotive Housings(636)



Connector Seals & Cavity Plugs(10)



Other Automotive Connector Accessories(17)

Customers Also Bought



TE Part #CAT-D48-ST273
DEUTSCH Connector Solid Contacts



TE Part #DT04-2P
REC, 2P, GRY, N




TE Part #DT06-2S
PLG, 2P, GRY, N



TE Part #CAT-D487-W416
Wedgelocks: DEUTSCH DT



TE Part #114017-ZZ
SEALING PLUG, SIZE 12/16, WHT



TE Part #281934-2
SINGLE WIRE SEAL



TE Part #CAT-AM71-CH8172
AMP SUPERSEAL 1.5MM, CONNECTOR HOUSING

Documents

Product Drawings

REC, 14P, BLK, E, 4/12/16, S

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_HDP24-24-14SE_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_HDP24-24-14SE_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_HDP24-24-14SE_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages

DEUTSCH HD30 & HDP20 CONNECTOR SERIES

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English