

## HFW1201K45

✓ ACTIVE



CII

TE Internal #: 2-1617031-0

General Purpose Signal Relay, DC, Non-Polarized, Monostable, 2  
Form C DPDT-CO, 2 A Contact Rating, 26.5 VDC Coil Voltage, 1 W  
Coil Power, Board Mount

[View on TE.com >](#)

Relays & Contactors > Electromechanical Relays

Relay & Contactor Type: **General Purpose Signal Relay**

Coil Magnetic System: **Non-Polarized, Monostable**

Contact Arrangement: 2 Form C DPDT-CO

Current Type: **DC**

Contact Current Rating: 2 A

## Features

## Product Type Features

| Relay & Contactor Type | General Purpose Signal Relay |
|------------------------|------------------------------|
|------------------------|------------------------------|

## Configuration Features

Contact Arrangement

2 Form C DPDT-CO

## Electrical Characteristics

|                        |              |
|------------------------|--------------|
| Coil Resistance        | 700 $\Omega$ |
| Contact Current Rating | 2 A          |
| Coil Voltage Rating    | 26.5 VDC     |
| Coil Power Rating DC   | 1 W          |

## Body Features

|                |                     |
|----------------|---------------------|
| Enclosure Type | Hermetically Sealed |
|----------------|---------------------|

## Termination Features

|                                    |             |
|------------------------------------|-------------|
| Main Termination & Connection Type | Solder Pins |
| Coil Termination & Connection Type | Solder Pins |

## Mechanical Attachment

| Product Mount Type | Board Mount |
|--------------------|-------------|
|--------------------|-------------|

## Usage Conditions

|                             |                            |
|-----------------------------|----------------------------|
| Operating Temperature Range | -65 – 125 °C[-85 – 257 °F] |
|-----------------------------|----------------------------|



|                                         |                |
|-----------------------------------------|----------------|
| Environmental Ambient Temperature (Max) | 125 °C[257 °F] |
|-----------------------------------------|----------------|

Operation/Application

|                      |                           |
|----------------------|---------------------------|
| Vibration Resistance | 30G's, 10 – 3000Hz        |
| Shock Resistance     | 100G's, 6ms               |
| Coil Magnetic System | Non-Polarized, Monostable |
| Current Type         | DC                        |

Other

|                         |            |
|-------------------------|------------|
| Contact Current Class   | ≤2 A       |
| Coil Power Rating Class | >.6 – ≤1 W |

Product Compliance

For compliance documentation, visit the product page on TE.com>

|                                               |                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Not Compliant                                                                                                                                                                                                                                                                                                                                                                                                            |
| EU ELV Directive 2000/53/EC                   | Not Compliant                                                                                                                                                                                                                                                                                                                                                                                                            |
| China RoHS 2 Directive MIIT Order No 32, 2016 | 有害物质含量超出标准 Restricted Substance(s) Above Threshold                                                                                                                                                                                                                                                                                                                                                                       |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2025 (250)<br>Candidate List Declared Against: JUNE 2025 (250)<br>SVHC > Threshold:<br>Pb (10% in Component)<br><b>Article Safe Usage Statements:</b><br>Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. |
| Halogen Content                               | Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free                                                                                                                                                                                                                                                                                                                                         |
| Solder Process Capability                     | Not lead free process capable                                                                                                                                                                                                                                                                                                                                                                                            |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>



Compatible Parts

|                                                                                                                                                |                                                                                                                                                  |                                                                                                                                                     |                                                                                                                                                  |
|------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
|  <p>TE Part # 1617150-5<br/>JMGSCD-18M = M39016/42-040M</p>   |  <p>TE Part # 4-1617599-9<br/>PRMGACG-26X=RELAY</p>             |  <p>TE Part # 5-1617592-9<br/>JMSPT-12XP=M28776/3-028P</p>       |  <p>TE Part # 1617543-1<br/>JMGSC-6PW=M39016/41-050P</p>      |
|  <p>TE Part # 7-1617592-0<br/>JMSPT-48XP=M28776/3-032P</p>   |  <p>TE Part # 1617541-3<br/>J1MSCD-26XLS=M39016/25-044L</p>   |  <p>TE Part # 6-1617573-5<br/>JMGSCG-5L=M39016/41-057L</p>      |  <p>TE Part # 5-1617600-6<br/>PRMGSCG-26X=RELAY</p>          |
|  <p>TE Part # 9-1617565-0<br/>J1MSP-6XM=M39016/10-020M</p>  |  <p>TE Part # 9-1617599-0<br/>PRMGSC-9X=RELAY</p>             |  <p>TE Part # 9-1617597-9<br/>PR1MSCT-40X=RELAY</p>            |  <p>TE Part # 5-1617591-9<br/>J1MSWT-26XM=M28776/4-022M</p> |
|  <p>TE Part # 2-1617601-7<br/>PRMSCDD-9X=RELAY</p>          |  <p>TE Part # 4-1617600-9<br/>PRMGSCDG-6XW=RELAY</p>          |  <p>TE Part # 3-1617571-5<br/>JMGACG-26MW=M39016/17-054M</p>   |  <p>TE Part # 3-1617599-8<br/>PRMGACDG-26XW=RELAY</p>       |
|  <p>TE Part # 4-1617572-4<br/>JMGSCDD-9M=M39016/43-035M</p> |  <p>TE Part # 2-1617573-3<br/>JMGSCDG-48PW=M39016/42-070P</p> |  <p>TE Part # 5-1617572-6<br/>JMGSCDDG-18MW=M39016/43-069M</p> |  <p>TE Part # 9-1617571-9<br/>JMGSC-9P=M39016/41-039P</p>   |

Customers Also Bought

HFW1201K45

General Purpose Signal Relay, DC, Non-Polarized, Monostable, 2 Form C DPDT-CO, 2 A Contact Rating, 26.5 VDC Coil Voltage, 1 W Coil Power, Board Mount



TE Part #ZPF000000000007992  
983-1Y 08-03 P6

TE Part #ZPF000000000018816  
FDBA 53H 8-3A-PX-K

TE Part #213499-1  
PLUG HSG,8 POWER METRIMATE

TE Part #532434-9  
HDI RECP ASSY 4 ROW 240 POS

TE Part #4-1617108-0  
PRMSC-26X = PRMS COTS SENSITIV

TE Part #5-1617786-8  
FCB-205-0227L=M83536/2-027L

TE Part #5532434-9  
ASSY,RECPT,R.ANGLE,HDI,LEAD-FR

TE Part #2-1617031-7  
HFW1201K56 = HFW 1/2 SIZE RELA

TE Part #2-1617036-0  
HFW4A1201S14 = HFW4A RELAY

TE Part #2157447-1  
RECT QUADRAX RCPT ASSY,2Q2, LOW PROF

Documents

Product Drawings

HFW1201K45 = M39016/6-109L

English

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_2-1617031-0\_D.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_2-1617031-0\_D.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_2-1617031-0\_D.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

HFW1201K45

General Purpose Signal Relay, DC, Non-Polarized, Monostable, 2 Form C DPDT-CO,  
2 A Contact Rating, 26.5 VDC Coil Voltage, 1 W Coil Power, Board Mount



[5-1773450-5\\_sec1\\_HFW](#)

English