

Honeywell Sensing and Control

Search

narrow your search

Products

- Controls Monitoring and Lighting (352)
- Machine Safety (1702)
- Sensors (6223)
- Switches (9750)
- Wireless (21)

Technology

- Capacitive (26)
- Electromechanical (9301)
- Microstructure (1486)
- NTC Thermistors (147)
- Thick Film (1764)
- More...

new products

New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site
WGLA and WPMM
XYR6000™
find out more

white papers

▶ Wireless Switches Offer Unlimited Benefit

▶ Basic Switches Are Not Created Equal

▶ Applying Precision Switches

▶ Sensors for Medical Devices

▶ New Ways to Measure Torque

▶ Choosing Safety Switches

▶ Specifying Hour Meters

Need help?

Click here to contact us

HOA6972-N51
Optoschmitt Sensors (Transmissive)
(Home : Products)



Actual product appearance may vary.

Sales & Service

Distributor Inventory

Overview

Specs

Documentation

Application Notes

Product Specifications

Series Name	HOA696X/HOA697X
Product Type	IR Switch
Output	Totem-Pole
Output Logic	Inverter
Mounting Configuration	No Mounting Tab
Package Components	Plastic
Package Color	Black
Continuous Forward Current	50 mA
Forward Voltage	1.6 V
Reverse Breakdown Voltage	3 V
Reverse Current	10 µA
Maximum Trigger Current	15 mA
Housing Material	Polysulfone, Opaque
Power Dissipation	100 mW
Operating Temperature	-40 °C to 70 °C [-40 °F to 158 °F]
Hysteresis (H)	0.05
Operating Supply Voltage	4.5 V to 7.0 V
Supply Voltage	7.0 Vdc
High Level Output Voltage	2.4 V minimum
High Level Supply Current	15 mA
Low Level Output Voltage	0.4 V maximum
Low Level Supply Current	15 mA
Short Circuit Output Current	-20 mA to -100 mA
Output Rise Time	70 ns
Output Fall Time	70 ns
Propagation Delay; Low-High; High-Low	5.0 µs
Duration of Output Short Vcc or Ground	1.0 second
IRET Trigger Current	15 mA
Comment	Output is HI when incident light intensity is above the turn-on threshold level.
Availability	Global
Sensor Aperture	1,52 mm x 0,25 mm [0.060 in x 0.010 in]
Slot Width	3,18 mm [0.125 in]

contacts

▶ Customer Service

▶ Technical Support

▶ Global Sales & Service

▶ View Site Demo

▶ Site Comments?

meet dr. larry

VIDEO - Dr. Larry Goldstein explains our newest and best technologies.



▶ Meet Dr. Larry

my links

▶ Login to iCOM

▶ Login as Rep/AD

▶ Login as Guest

▶ Login to Digital University

News Center

▶ HONEYWELL ANNOUNCES ADDITION TO RELIALIGN™ RESIDENTIAL DOOR INTERLOCK SWITCHES THAT FEATURE RUGGED, PLASTIC HOUSING

▶ HONEYWELL RELEASES UNLIMITED POTENTIAL WITH NEW LIMITLESS™ WIRELESS SWITCHES

▶ HONEYWELL'S XYR6000 WIRELESS POSITION SENSOR ENABLES MONITORING IN HAZARDOUS AREAS AND REMOTE LOCATIONS

MICRO SWITCH Anniversary site

Terms & Conditions | Privacy Statement | Site Map

http://sensing.honeywell.com/index.cfm?ci_id=140301&la_id=1&pr_id=152608

8/29/2010 11:26:00 AM