15/20 Watts

JTK Series



- Very High Power Density
- Wide 4:1 Input Range
- Operating Temperature –40 °C to +100 °C
- Single & Dual Outputs
- 1600 VDC Isolation
- UL Approved
- High Efficiency – up to 89%
- 3 Year Warranty

Specification

Input

Input Voltage Range	• 24 V (9-36 VDC) 48 V (18-75 VDC)
Input Current	• See table
Input Filter	• Pi network
Input Reflected Ripple Current	• JTK15: 20 mA pk-pk JTK20: 30 mA pk-pk through 12 µH inductor and 47 µF capacitor, 5 Hz to 20 MHz
Input Surge	• 24 V models: 50 VDC for 100 ms • 48 V models: 100 VDC for 100 ms

Output

Output Voltage	• See table
Output Trim	• ±10% max on single output
Minimum Load	• No minimum load required
Initial Set Accuracy	• ±1% max
Start Up Delay	• 20 ms typical
Line Regulation	• JTK15: ±0.2% max single, ±0.5% max dual JTK20: ±0.5% max
Load Regulation	• ±0.5% max single, ±1.0% max dual
Cross Regulation	• ±5% on dual output models, (see note 2)
Transient Response	• <3% max deviation, recovery to within 1% in 250 µs for a 25% load change
Ripple & Noise	• 100 mV pk-pk, 20 MHz bandwidth, (see note 3)
Overload Protection	• JTK15: 170% of full load typical, JTK20: 150% of full load typical
Overvoltage Protection	• 3.3 V models: 3.9 V typical 5 V models: 6.2 V typical 12 V models: 15 V typical 15 V models: 18 V typical ±5 V models: ±6.2 V typical ±12 V models: ±15 V typical ±15 V models: ±18 V typical
Short Circuit Protection	• Trip & restart (hiccup) with auto recovery
Maximum Capacitive Load	• See table
Temperature Coefficient	• ±0.02%/°C max
Remote On/Off	• On >3.0 VDC or open circuit Off <1.2 VDC or short circuit pins 2 & 3

General

Efficiency	• See table
Isolation	• 1600 VDC Input to Output 1600 VDC Input to Case 1600 VDC Output to Case
Isolation Capacitance	• JTK15: 1200 pF max JTK20: 1000 pF max
Switching Frequency	• JTK15: 375 kHz typical JTK20: 330 kHz typical
Power Density	• JTK15: 38.4 W/in³, JTK20: 51.3 W/in³
MTBF	• >560 KHrs to MIL-STD-217F at 25 °C, GB

Environmental

Operating Temperature	• -40 °C to +100 °C, JTK15: derate from 100% load at +65 °C to no load at +100 °C, JTK20: derate from 100% load at +55 °C to no load at +100 °C
Case Temperature	• +105 °C max
Storage Temperature	• -40 °C to +125 °C
Humidity	• Up to 90%, non-condensing
Cooling	• Natural convection

EMC

Emissions	• EN55022, Level A conducted & radiated with external components - see applications note
ESD Immunity	• EN61000-4-2, Level 2 Perf Criteria A
Radiated Immunity	• EN61000-4-3, 3 V/m Perf Criteria A
EFT/Burst	• EN61000-4-4, Level 3 Perf Criteria A*
Conducted Immunity	• EN61000-4-6, 3 V rms Perf Criteria A
Magnetic Fields	• EN61000-4-8, 1 A/m Perf Criteria A

Safety

Safety Approvals	• UL60950-1, CAN/CSA C22.2 No.60950-1, UL62368-1, CE (Meets all applicable directives), UKCA (Meets all applicable legislation)

**External input capacitor required 220 µF / 100 V.*


Models and Ratings

Input Voltage	Output Voltage	Output Current	Input Current[1]		Maximum Capacitive Load	Efficiency	Model Number
			No Load	Full Load			
9-36 V	3.3 V	4.000 A	15 mA	647 mA	1000 µF	86%	JTK1524S3V3
	5.0 V	3.000 A	15 mA	727 mA	1000 µF	87%	JTK1524S05
	12.0 V	1.300 A	15 mA	747 mA	330 µF	88%	JTK1524S12
	15.0 V	1.000 A	15 mA	710 mA	220 µF	89%	JTK1524S15
	±5.0 V	±1.500 A	15 mA	744 mA	±470 µF	85%	JTK1524D05
	±12.0 V	±0.625 A	15 mA	720 mA	±220 µF	88%	JTK1524D12
	±15.0 V	±0.500 A	15 mA	710 mA	±100 µF	89%	JTK1524D15
18-75 V	3.3 V	4.000 A	10 mA	331 mA	1000 µF	84%	JTK1548S3V3
	5.0 V	3.000 A	10 mA	368 mA	1000 µF	86%	JTK1548S05
	12.0 V	1.300 A	10 mA	378 mA	330 µF	87%	JTK1548S12
	15.0 V	1.000 A	10 mA	360 mA	220 µF	88%	JTK1548S15
	±5.0 V	±1.500 A	10 mA	377 mA	±470 µF	84%	JTK1548D05
	±12.0 V	±0.625 A	10 mA	363 mA	±220 µF	87%	JTK1548D12
	±15.0 V	±0.500 A	10 mA	360 mA	±100 µF	88%	JTK1548D15
9-36 V	3.3 V	4.500 A	50 mA	720 mA	10000 µF	86%	JTK2024S3V3
	5.0 V	4.000 A	50 mA	936 mA	5000 µF	89%	JTK2024S05
	12.0 V	1.670 A	22 mA	936 mA	850 µF	89%	JTK2024S12
	15.0 V	1.330 A	22 mA	936 mA	700 µF	89%	JTK2024S15
	±12.0 V	±0.833 A	25 mA	936 mA	±470 µF	89%	JTK2024D12
	±15.0 V	±0.667 A	25 mA	936 mA	±330 µF	89%	JTK2024D15
18-75 V	3.3 V	4.500 A	30 mA	309 mA	10000 µF	86%	JTK2048S3V3
	5.0 V	4.000 A	30 mA	468 mA	5000 µF	89%	JTK2048S05
	12.0 V	1.670 A	15 mA	468 mA	850 µF	89%	JTK2048S12
	15.0 V	1.330 A	15 mA	468 mA	700 µF	90%	JTK2048S15
	±12.0 V	±0.833 A	15 mA	468 mA	±470 µF	89%	JTK2048D12
	±15.0 V	±0.667 A	15 mA	468 mA	±330 µF	89%	JTK2048D15

Notes

1. Input current measured at nominal 24 V and 48 V input.
2. When one output is set to 100% load, and the other varies between 25% and 100% load.
3. Measured with 1 µF ceramic capacitor and 10 µF tantalum capacitor across output rails.

Mechanical Details




Pin Connections		
Pin	Single	Dual
1	+Vin	+Vin
2	-Vin	-Vin
3	Remote On/Off	Remote On/Off
4	+Vout	+Vout
5	Trim	Com
6	-Vout	-Vout

Notes

1. All dimensions are in inches (mm)
2. Weight: 0.04 lbs (20 g) approx.
3. Pin diameter: 0.04 ±0.002 (1.0 ±0.05)
4. Pin pitch tolerance: ±0.014 (±0.35)
5. Case tolerance: ±0.02 (±0.5)

Application Notes

Output Trim



Trim Resistor Values		
Model Number	Trim up 10%	Trim down 10%
JTK - S3V3	8 k	12 k
JTK - S05	10 k	5 k
JTK - S12	20 k	7 k
JTK - S15	20 k	6 k

Approximate values.

Output can be externally trimmed by using this method.
(Single output models only). For variable trimming, use 100 kΩ potentiometer.
Contact sales for details.

Input Filter

