| REV. | ECN NO. | DATE | SIGN | DESCRIPTION |
|---|---|---|---|---|
| C | C210024 | 2021/01/12 | Vicky | △C X1 |
| D | C210235 | 2021/03/24 | Ruru | △D X2 |
| E | C222001 | 2022/12/29 | Ruru | △E X2 |






| Pin Out | | |
|---|---|---|
| 5 | Gary | 灰 |
| 4 | Black | 黑 |
| 3 | Blue | 藍 |
| 2 | White | 白 |
| 1 | Brown | 棕 |
| Pin # | Wire | |

C2




5P

C1




5P

Pin Assignments Front View

△B MI2BXXML-12BFL-SBXXX

XX: No. Of Pin

XXX: 0.5~99Meters
A05: 0.5 Meter
001: 1 Meter
002: 2 Meters
:
099: 99 Meters

Note: △B △C △D
* RoHS Compliant
* QC Important dimension
* C1
△E Waterproof rate: IP68, mated 1m/24h
IP69K, mated
Housing: Thermoplastic, Black
Pin: Copper alloy, Gold plated
Nut: Metal
Outer mold: Thermoplastic, Black
* C2
△E Waterproof rate: IP68, mated 1m/24h
IP69K, mated
Housing: Thermoplastic, Black
Pin: Copper alloy, Gold plated
O-Ring: Rubber, Green
Nut: Metal
Outer mold: Thermoplastic, Black
* Cable: UL20549, 22#*5C, OD=4.4mm, PUR Jacket, Black
* Cable length tolerance: 0.5M < L ≦ 1M: +60/-0 mm
1M < L ≦ 3M: +120/-0 mm
3M < L ≦ 5M: +160/-0 mm
5M < L ≦ 10M: ±100 mm
10M < L ≦ 20M: ±200 mm
20M < L ≦ 30M: ±300 mm
30M < L ≦ 99M: ±500 mm

UNIT: mm

TOLERANCE
±0.5 mm

TITLE: ACC, SEN, B Code, DB-ENDED MF △D

SCALE: 1:2 | SIZE: A4 | SHEET: 1 OF 1

REV.: E | WC-REV.:

QC: Inspection item

**Amphenol LTW**
安費諾亮泰企業股份有限公司

| ITEM NO | DRAWN BY | DATE |
|---|---|---|
| | Vicky | 2018-12-11 |
| DWG NO: △B MI2BXXML-12BFL-SBXXX | CHECKED BY: Rita | DATE: 2018-12-11 |
| CUSTOMER: ALTW | APPROVED BY: Max | DATE: 2018-12-11 |

WI0814-03-RW01A2

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.