



HEPTABAND™ MAF9430x Series

Wireless Antenna

**815-885 MHz/ 824-894 MHz/ 880-960 MHz/
1427-1511 MHz/ 1575 MHz/ 1710-1880 MHz/
1850-990 MHz/ 1920-2170 MHz/
2400-2500 MHz**

MAF9430x Series heptaband portable wireless antennas provide excellent radio transmission characteristics while offering the ultra flexibility of more than seven bands in one profile. With operating frequencies of 815- 885 MHz, 824-894 MHz, 880-960 MHz, 1427-1511 MHz, 1575 MHz, 1710-1880 MHz, 1850-1990 MHz, 1920-2170 MHz, and 2400-2500 MHz, the antenna is the ideal choice when multiple bandwidths are required in various regional and global applications. Additionally, the blade style antenna features both knuckle and swivel snap-in or SMA/TNC/RPTNC connector options.

FEATURES AND BENEFITS

- Operates simultaneously in more than seven frequency bands supporting cellular, Quadband GSM+UMTS/3G, GPS, AWS, Wi-Fi, WLAN, and WISP
- Available in knuckle swivel snap or SMA/TNC/RPTNC connector options.
- Blade style external antenna measures only 6.33 inches

APPLICATION

- Wireless terminal
- Point-of-sale
- Machine-to-machine
- Automatic meter reading
- Home security

ELECTRICAL SPECIFICATIONS


Model Name	Heptaband
Operating Frequency (MHz)	815-885 MHz, 824-894 MHz, 880-960 MHz, 1427-1511 MHz, 1575 MHz, 1710-1880 MHz, 1850-1990 MHz, 1920-2170 MHz, and 2400-2500 MHz
Gain (dBi)	1-3
VSWR	<2.5:1
Polarization	Linear
Azimuth - 3 dB Beamwidth	Omnidirectional
Nominal Impedance (Ohms)	50
Max Power - Ambient 25°C (W)	10

MECHANICAL AND ENVIRONMENTAL SPECIFICATIONS


Dimensions – mm (inches)	161 x 9.3 (6.3 x 0.36)
Mounting Style	Snap-in/Captive, SMA, RPSMA, TNC, RPTNC
Operating Temperature – °C (°F)	-5 to +50°C (-23 to +122°F)
Material Substance Compliance	RoHS

CONFIGURATION

MODEL NUMBER	PART NUMBER	CONNECTOR	COLOR
HEPTA-SM	MAF94300	SMA	Black
HEPTA-RSM	MAF94301	RP-SMA	Black



TYPICAL ELEVATION PATTERN



TYPICAL AZIMUTH PATTERN

TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE, TE Connectivity, TE connectivity (logo), and EVERY CONNECTION COUNTS are trademarks owned or licensed by the TE Connectivity plc family of companies. Other product names, logos, and company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, complete, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. In no event will TE be liable for any direct, indirect, incidental, special or consequential damages arising from or related to recipient's use of the information. It is the sole responsibility of recipient of this information to verify the results of this information using their engineering and product environment. Recipient assumes any and all risks associated with the use of the information. Antenna performance may vary. TE is a component manufacturer, and customer and/or end-user is responsible for all end-use compliance and regulatory requirements.

©2025 TE Connectivity. All Rights Reserved.