

1		2		3		4		5		6		7		8	
				REV.		ECN NO.		DATE		SIGN		DESCRIPTION			
				A				2019/08/09		Xiaofeng		Initial Release			
				B		C200426		2020/04/08		Xiaofeng		B XI			

PE Bag

Pin Assignments
Front View

360 Adjustable Key Code Direction

Note:

- * IP: IP67.
- * Housing: Thermoplastic, Black.
- * Female Pin: Copper Alloy, Gold Plated.
- * O-Ring: Silicone, Grey.
- * Clamp Ring: Zinc Alloy, Nickel Plated.
- * Sealing Nut: Zinc Alloy, Nickel Plated.
- * Seal For Cable OD: $\varnothing 4.0\text{mm} \sim \varnothing 7.0\text{mm}$
- * Applicable Wire gauge (Stranded wire cross section) 20AWG ~ 24AWG
- * Mating Recommended tightening torque: 3~4 kgf.cm / 0.29~0.39 N.m
- * Sealing-Nut Recommended tightening torque: 4~6 kgf.cm / 0.39~0.59 N.m
- * Detailed applicable wire specifications may vary depending on the actual wire construction.

UNIT:mm				TITLE		Amphenol LTW 安費諾亮泰企業股份有限公司		ITEM NO		DRAWN BY		DATE	
TOLERANCE				MI2 D-Code Shielded Assy 4PIN F Conn. F Pin				MSDS-04BFFC-SR7001		Xiaofeng		2019/08/09	
$\pm 0.5\text{mm}$		SCALE Free		SIZE A4				DWG NO		CHECKED BY		DATE	
		REV. B		WC-REV. .0				MSDS-04BFFC-SR7001		Li-Feng		2019/08/09	
				SHEET 1 OF 1				CUSTOMER		APPROVED BY		DATE	
				QC: Inspection item				ALTW		Jerry		2019/08/09	

1

2

3

4

5

6

7

8

W10814-03-BW01A2

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.