




PT-6

6-mm carbon through-hole trimmer potentiometer




KEY FEATURES

- ▶ Excellent performance
- ▶ Carbon resistive element
- ▶ Up to 10 mechanical detents
- ▶ Up to 10.000 life cycles
- ▶ IP54 protection
- ▶ Magazine packaging for automatic insertion
- ▶ Polyester substrate
- ▶ Wiper positioned at the initial, 50% or fully clockwise position
- ▶ Loose or assembled shaft and knobs
- ▶ Linear, logarithmic and antilogarithmic tapers
- ▶ SPDT switch function

On request

- ▶ Embossed tape packaging



The **only 6 mm miniature trimmer**
potentiometer with optional
stop positions for haptic feedback.

ELECTRICAL SPECIFICATIONS

Taper*	Lin, Log, Alog
Range of values*	(Decad. 1.0 - 2.0 - 2.2 - 2.5 - 4.7 - 5.0)
Lin	$220\Omega \leq R_n \leq 5M\Omega$
Log, Alog	$1K\Omega \leq R_n \leq 5M\Omega$
Tolerance*	
$220\Omega \leq R_n \leq 1M\Omega$	$\pm 20\%$
$1M\Omega < R_n \leq 5M\Omega$	$\pm 30\%$
Max. Voltage	
Lin	100 VDC
Log, Alog	50 VDC
Nominal power 50°C (122°F)	
Lin	0.1 W
Log, Alog	0.05 W
Residual resistance	$\leq 0.5\% R_n$ (5Ω min.)
Equivalent noise resistance	$\leq 3\% R_n$ (30Ω min.)
Operating temperature**	-25°C to +70°C (-13°F to + 158°F)

* Others available on request

** Up to 85°C depending on application.

POTENTIAL APPLICATIONS

- ▶ Appliance program selection
- ▶ Thermostat adjustment
- ▶ Timer and control relays
- ▶ Consumer electronics
- ▶ Power tool controls
- ▶ Test and measurement equipment
- ▶ Alarms and detectors
- ▶ Circuit breakers

PT-6

6-mm carbon through-hole trimmer potentiometer

MECHANICAL SPECIFICATIONS	
Mechanical rotation angle	$235^{\circ} \pm 5^{\circ}$
Electrical rotation angle*	$200^{\circ} \pm 20^{\circ}$
Torque Rotational Stop	0.2 to 2 Ncm (0.3 to 2.7 in-oz) > 4 Ncm (>7 in-oz)
Life**	up to 10,000 cycles


*Increased rotational angle of $215^{\circ} \pm 20^{\circ}$ available upon request ** Others available on request

ENVIRONMENTAL TESTING		
	Test conditions (CEI 393-1)	$\Delta R(\%)$ - Typical test results
Electrical life	1,000h at 50°C ; 0.1 W	$\pm 5\%$
Mechanical life	1,000 cycles at 10 to 15 cpm	$\pm 3\%$ ($R_n < 1\text{M}$)
Temperature coefficient	-25°C to $+70^{\circ}\text{C}$	± 300 ppm/ $^{\circ}\text{C}$ ($R_n < 100\text{K}$)
Thermal cycling	16h at 85°C and 2h at -25°C	$\pm 2.5\%$
Damp heat	500 h at 40°C and 95% relative humidity (RH)	$\pm 5\%$
Vibration	2h each plane at 10Hz - 55Hz	$\pm 2\%$
Storage	6 months at $23^{\circ}\text{C} \pm 2^{\circ}\text{C}$ and 50% RH	$\pm 2.5\%$


Out of range values may not comply with these results. Standard test conditions: temperature: $23^{\circ}\text{C} \pm 2^{\circ}\text{C}$ and 45% to 70% RH.
Mechanical life of detented versions is 100 cycles

RECOMMENDED CONNECTIONS

Recommended connection circuit for a position sensor or control application (voltage divider circuit electronic design).



POWER RATING CURVE



PT-6

6-mm carbon through-hole trimmer potentiometer

HOW TO ORDER

Example: PT6KV-221A2020

PT6

Series

—

Rotors¹

Mounting method

Ω-Value²

—

Taper

Tolerance³

Optional features

—

Detents⁴

Packaging⁵

Shaft/Knob color⁶

Wiper position

Life

Shaft/Knob

Crimping

A
K
M
Q
W | inserted knob / shaft
X

H = horizontal adjust
V = vertical adjust

221 = 220Ω
...
505 = 5MΩ
000 = CM

A = lin.
B = log.
C = alog.

0505 = ±5%
0707 = ±7%
1010 = ±10%
2020 = ±20%
3030 = ±30%
XXYY = +XX-YY%

[empty]
P04
P05
P06
P07
P08
P10

[empty] = bulk
T = magazines

[empty]
CR = cream
GR = grey
IN = natural
NE = black

[empty] = initial
PM = 50%
PF = final


[empty] = 1K cycles
E = 10K cycles

[empty] = none
1 = Fig.1
2 = Fig.2
...
6 = Fig.6

[empty] = crimped
SC = straight

1. Rotors: "X" rotor only available on "H" mounting versions. Default color is white. Other rotor colours on request.
2. Ω- Value: XXX - First two digits of Ω-value 000 = CM = switch SPDT version
XXX - Number of zeros
3. Tolerance: for custom tolerance please check availability at info@piher.net
4. Detents: Detented versions use purple rotor color (rotor color code "VI"). Ordering code example: PT6KH-254A2020-P04-VI
5. Packaging: Only for "V" mounting method. "W" rotor with shaft Fig. 2 is not available in magazines. Embossed tape packaging on request.
6. Default colour for knob/shaft is cream

 [check inventory](#)









DEFAULT CONFIGURATION	
PT-6	
Life	1.000 cycles (forth and back the mechanical angle travel)
Detents	none
Housing color	black
Rotor color	white
Wiper Position	initial
Packaging	bulk

ORDER CODE EXAMPLES	
PT6WV-104A1010-5NE-SC	
6mm potentiometer with factory pre-inserted knob, V mounting method (vertical adjustment), 100K resistive value, linear taper, 10% resistive tolerance, black knob ref. 6148 and straight terminals (not crimped).	
PT6KH-103A2020	
6mm potentiometer with rotor "K" (cross shape), H mounting method (horizontal adjustment), 10K resistive value, linear taper, 20% resistive tolerance and crimped terminals.	

PT-6


6-mm carbon through-hole trimmer potentiometer

ROTORS			
K Cross slot through hole	Q Cross slot through hole colour: pink	M Hexagonal through hole	A Hexagonal through hole colour: pink
			
X Adjustable from collector side		W Adjustable from terminal side	
 With inserted knob / shaft. Example with knob ref. 5155		 With inserted knob / shaft. Example with knob ref. 5155	


Default delivery is at initial position. Wipers are shown positioned at 50% for the picture.

MOUNTING METHOD


V = Vertical Adjustment - Horizontal Mounting



H = Horizontal Adjustment - Vertical Mounting





Download STEP files here:
www.pihernet.net





PT-6

6-mm carbon through-hole trimmer potentiometer

CRIMPING

Crimped	Non-crimped						
 <table border="1" data-bbox="462 515 702 616"> <thead> <tr> <th></th><th>X</th></tr> </thead> <tbody> <tr> <td>Terminals</td><td>0.25</td></tr> <tr> <td>Collector (S)</td><td>0.30</td></tr> </tbody> </table>		X	Terminals	0.25	Collector (S)	0.30	
	X						
Terminals	0.25						
Collector (S)	0.30						

SMD MOUNTING AVAILABLE



PS-6	N-6
	

For more information visit: www.piher.net

STANDARD RESISTANCE-VALUES AND TOLERANCES



Resistance Ω	100	200	220	250	470	500	1K	2K	2.2K	2.5K	4.7K	5K	10K	20K	22K	25K	47K	50K	100K	200K	220K	250K	470K	500K	1M	2M	2.5M	4.7M	5M
Order Code	101	201	221	251	471	501	102	202	222	252	472	502	103	203	223	253	473	503	104	204	224	254	474	504	105	205	255	475	505
Tolerance	30%		20%																							30%			

TAPERS

Standard	Example: special custom taper
A = Linear B = Log. C = Alog. 	

For more information on custom tapers contact Piher Sensing Systems.

SWITCH VERSION



PT-6

6-mm carbon through-hole trimmer potentiometer

DETENTS / STOP POSITIONS

P04	P05	P06	P07	P08	P10

— Relative detent positions along total mechanical travel

All detented versions will be studied case by case, more than 10 detents available on request.
 Unless otherwise specified the detents are evenly spaced (using the end points as reference).
 Standard mechanical life of detented versions: 100 cycles. Long life versions are available on request.
 Detent torque can vary from 1.2 to 2.5 times the standard potentiometer torque.
 Rotor color of detented versions is purple-violet.




PACKAGING

Bulk (1000 units per box)	Magazine / Automatic Insertion (80 units per magazine)	
All models	PT-6 V models	PT-6 WV models

Dimensions (mm): 185x85x40


Embossed tape/reel packaging on request.

WIPER POSITION



Wiper positioning on initial position is standard. Special delivery positions available on request.

DUAL GANG METAL SHAFT ON REQUEST - REF.: 6060



PT-6

6-mm carbon through-hole trimmer potentiometer

KNOBS / SHAFTS (FOR K ROTOR)	
Fig. 1 - Ref.: 5155 Colors available: white, cream and black. Default color: white.	Fig. 2 - Ref. 6132 Shaft - Not suitable for magazine packaging Colours*: cream and black. Other colours upon request.
Fig. 3 - Ref.: 5141 Color: grey*	Fig. 4 - Ref.: 6172 Color*: grey
Fig. 5 - Ref.: 6148 For V models only. Colors available: cream and black. Default color: cream. Position of the wiper.	Fig. 6 - Ref.: 6160 For V models only. Colors available: cream and black. Default color: cream.

If you wish to use your own plastic shaft/knob/actuator please contact Piher Sensing Systems for advice about compatible materials.

Shaft and knobs (Fig 1 to 4) are delivered unassembled if not specified otherwise in part number code ("W" or "X"). The position of assembled knobs can be indicated in part number code: Initial (default), 50% (PM) or Final (PF). Mounted shaft fig. 2 will be delivered by default at random position. Custom specific positions are available for shaft and all knobs on request.

* We offer this product in other colors. Please contact us at info@piher.net to check availability.



Please always use the latest updated datasheets and 3D models published on our website.

Disclaimer:

The product information in this catalog is for reference purposes. Please consult for the most up to date and accurate design information.
Piher-Sensors & Controls S.A., its affiliates, agents, and employees, and all persons acting on its or their behalf collectively, ("Piher"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product described herein.
Piher disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Piher's terms and conditions of sale, including but not limited to the warranty expressed therein, which apply to these products.
No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Piher.
The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Piher products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Piher for any damages arising or resulting from such use or sale. Please contact authorized Piher personnel to obtain written terms and conditions regarding products designed for such applications.
Product names and markings noted herein may be trademarks of their respective owners. Information contained in and/or attached to this catalogue may be subject to export control regulations of the European Community, USA, or other countries. Each recipient of this document is responsible to ensure that usage and/or transfer of any information contained in this document complies with all relevant export control regulations. If you are in any doubt about the export control restrictions that apply to this information, please contact the sender immediately. For any Piher Exports, Note: All products / technologies are EAR99 Classified commodities. Exports from the United States are in accordance with the Export Administration Regulations. Diversion contrary to US law is prohibited.

Rev:110326 © Piher Sensors & Controls S.A.

Piher Sensing Systems
Polígono Industrial Municipal
Vial T2, N°22
31500 Tudela, Spain

sales@piher.net
+34 948 820 450



NEED QUICK HELP?
Our AI Virtual Assistant is available
24/7 to provide instant support—
visit chat.piher.info to chat now!