


PXM6034/B Datasheet

Product Name // Rewireable Flex Connector PXM6034
Series 4mm-7mm Cable Metal Body

 [View Product Page](#)



// Product Description:	
- Rewireable Flex Cable Connectors - Water and dustproof to IP66, IP68, IP69K when mated with compatible connector 30 degree push twist locking, tamperproof lock prevents accidental un-mating - Supplied with shielded RJ45 plug - Choice of cable acceptance depending on part code: - Part codes suffixed /A have cable glands optimised for PUR jacket cable to maintain CAT5e performance	- Part codes suffixed /B accept cable 4mm-7mm diameter - Choice of body material depending on part code: - Plastic body (part codes prefixed PXP) - Metal body (part codes prefixed PXM) - PXP6081/PXM6081 Sealing Cap available separately to maintain IP rating of unmated connectors - Mate with PXP6033TP, PXP6033TP/E, PXM6033TP Front Panel Mount CAT5e Couplers

// General Information:	
Product Display Title: Product Family: Product Series: Body Material: Body Material Type: Contact Type: Coupling Type: Current Max: Diameter Over Coupling Ring Mm: Ethernet Category: Function: Ip Rating: Max Cable Entry Size: Min Cable Entry Size: Max Operating Temperature: Min Operating Temperature: Number Of Contacts: Voltage Max:	Rewireable Flex Cable Connectors Circular Data Connectors 6000 Series - Ethernet Buccaneer Brass - Nickel Plated Metal Body Plug Contact Push-Twist 1.5A 32mm Cat 5e Flex Cable Connector IP66, IP68, IP69K 7mm 4mm +70°C -20°C 8 Contacts 42V

// Product PDF Links

 6000 Series Ethernet connectors...

 6000 Series Ethernet connectors...

// Product 3D CAD Model Links

 PXM6034/B3D CAD Model