


REVISIONS			
REV	DESCRIPTION, ECN, EAR NO.	DATE	APP'D
A	PROPOSAL	OCT08/19	L.CHAN







RECOMMENDED PANEL CUTOUT




BI-COLOUR LED DETAIL
(RED/YELLOW AND GREEN/ORANGE LED'S ARE ALSO AVAILABLE)



RECOMMENDED P.C.B. LAYOUT
(COMPONENT SIDE OF BOARD)





LED SCHEMATIC

MATERIALS:
PLASTIC HOUSING: HIGH TEMPERATURE THERMOPLASTIC
FLAMMABILITY RATING UL 94V-0
CONTACTS: PHOSPHOR BRONZE
PLATING: 50 µ" [1.27 MICRONS]
MIN. GOLD ON MATING SURFACES.
50 µ" [1.27 MICRONS]
MIN. NICKEL UNDERPLATE
100 µ" [2.54 MICRONS]
MIN. MATTE TIN ON CONTACT TAILS.
SHIELD: STAINLESS STEEL WITH TIN FINISH ON PCB TAIL.


PART NUMBER: RJHSE-746X
REFER TO LED OPTIONS DRAWING
FOR ORDERING CODES

AMPHENOL CANADA CORP
RoHS COMPLIANT
2011/65/EU RECAST

UNLESS SPECIFIED OTHERWISE	DRAWN W.QIU	DATE OCT08/19	Amphenol Canada Corp. Commercial Products
PRIMARY UNITS INCH	CHECKED L.CHAN	OCT08/19	
SECONDARY MILLIMETER	M.E. APP'D		TITLE: HIGH SPEED MODULAR JACK, 6 POSITIONS, 6 STAMPED CONTACTS, SHIELDED, WITH LED'S – RoHS COMPLIANT
REFERENCE IN PARENTHESES	Q.A. APP'D		
GENERAL TOLERANCES	DWG APPR.		
1 DECIMAL PLACE ±0.025	ENG. REL. NO.		DWG. NO. P-RJHSE-746X REV A
2 DECIMAL PLACES ±0.020	REF.		
3 DECIMAL PLACES ±0.015	THIRD ANGLE PROJECTION	DO NOT SCALE DRAWING	CODE ID NO. 03554 DWG SIZE: C SCALE: N/A SHEET 1 OF 1
ANGULAR DEGREES ±1.0°			

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT WRITTEN PERMISSION FROM AMPHENOL CANADA CORP.

REV	DESCRIPTION, ECN, EAR NO.	DATE	APP'D
F	UPDATE SPEC	JUL06/18	L.CHAN
G	UPDATE SPEC	NOV19/18	L.CHAN
H	UPDATE SPEC	JAN29/19	L.CHAN



TYPICAL FOR SINGLE & MULTI-PORT



EXAMPLE:
PART NUMBER RJHSE-538X
LED COLOR CODE

CODE	LED 2 (LEFT)	LED 1 (RIGHT)	CODE	LED 2 (LEFT)	LED 1 (RIGHT)	CODE	LED 2 (LEFT)	LED 1 (RIGHT)
0	BLOCKED	BLOCKED	9	GREEN	BLOCKED	J	BiC RD/GR	YELLOW
1	YELLOW	GREEN	A	BiC GR/YE	BiC GR/YE	K	YELLOW	BiC GR/OR
2	BLOCKED	GREEN	B	BiC RD/GR	BiC RD/GR	L	BiC GR/YE	RED
3	YELLOW	BLOCKED	C	BiC RD/GR	BiC GR/YE	M	RED	YELLOW
4	GREEN	YELLOW	D	GREEN	BiC GR/YE	N	BiC GR/RD	BiC GR/YE
5	GREEN	GREEN	E	YELLOW	BiC GR/YE	P	GREEN	BiC RD/GR
6	YELLOW	YELLOW	F	BiC GR/YE	YELLOW	R	BiC GR/OR	GREEN
7	RED	GREEN	G	BiC GR/OR	BiC GR/OR	T	RED	RED
8	GREEN	RED	H	BiC GR/YE	GREEN	V	BiC RD/GR	GREEN
						W	ADDITIONAL	OPTIONS

EXAMPLE OF ADDITIONAL LED OPTIONS:
PART NUMBER RJHSE-538W-01Y
ADDITIONAL LED COLOR CODE
DENOTES ADDITIONAL LED OPTIONS TO BE USED

CODE	LED 2 (LEFT)	LED 1 (RIGHT)	CODE	LED 2 (LEFT)	LED 1 (RIGHT)	CODE	LED 2 (LEFT)	LED 1 (RIGHT)
0	DO NOT USE		F	GREEN	BiC GR/OR	A	LOWC YE	LOWC YE
1	RED	BLOCKED	R	BiC GR/RD	BiC GR/RD	B	LOWC YE	LOWC GR
2	BiC GR/OR	YELLOW	G	GREEN	ORANGE	C	LOWC GR	LOWC YE
3	YELLOW	RED	H	BiC OR/GR	BiC OR/GR	D	LOWC GR	LOWC GR
4	BLOCKED	RED	J	BiC YE/GR	BiC YE/GR	M	LOWC RD	LOWC YE
5	BLOCKED	YELLOW	K	BLOCKED	WHITE			
6	RED	BiC RD/GR	L	GREEN	BiC YE/GR			
7	BLOCKED	BiC RD/GR	N	BLUE	RED			
8	BiC RD/GR	BLOCKED	P	BLOCKED	BiC GR/YE			
9	BiC GR/YE	BLOCKED	T	BLOCKED	BiC YE/GR			
E	BiC GR/YE	BiC GR/RD						

LED SPECIFICATIONS:
FORWARD VOLTAGE: 2.1 VOLTS TYP.
FORWARD VOLTAGE: 2.9 VOLTS FOR WHITE
FORWARD VOLTAGE: 3.1 VOLTS FOR BLUE
REVERSE VOLTAGE: 5.0 VOLTS MIN.
LUMINOUS INTENSITY:
18.6 mcd MIN. (AT If=20mA) TYP.
480 mcd MIN. (AT If=5mA) FOR WHITE
110 mcd MIN. (AT If=20mA0 FOR BLUE

OPERATING TEMPERATURE: −55° TO 85° C
LEAD SOLDERING TEMPERATURE: 260° C
(5 SEC, 1/16" FROM CASE)
PLATING ON TAILS: TIN OR TIN/COPPER ALLOY OVER SILVER

PRIMARY COLOR FOR BI-COLOR LEDS IN STANDARD ANODE/CATHODE CONFIGURATION IS:
RED-GREEN= RED
RED-YELLOW= RED
GREEN-YELLOW= GREEN
GREEN-ORANGE= GREEN

LEGEND
BiC=BI-COLOR LED
LOWC=LOW CURRENT LED
YE=YELLOW
GR=GREEN
RD=RED
OR=ORANGE

NOTE:
THE TWO DIGITS PRECEDING THE ADDITIONAL LED CODE MUST BE USED IN THE PART NUMBER, WHEN ORDERING ANY OF THE ADDITIONAL LED OPTIONS.

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT WRITTEN PERMISSION FROM AMPHENOL CANADA CORP.

UNLESS SPECIFIED OTHERWISE	DRAWN K. LAMBIE	SEP21/04
PRIMARY UNITS INCHES	CHECKED	
SECONDARY MILLIMETERS	M.E. APP'D	
REFERENCE IN PARENTHESES	Q.A. APP'D	
GENERAL TOLERANCES	DWG APP'D	
1 DECIMAL PLACE ±0.025	ENG. REL. NO.	
2 DECIMAL PLACES ±0.02	REF.	
3 DECIMAL PLACES ±0.015	THIRD ANGLE PROJECTION	DO NOT SCALE DRAWING
ANGULAR DEGREES ±1°		

Amphenol Canada Corp.
Commercial Products

LED OPTIONS FOR RJHSE, SINGLE OR MULTI-PORT CONNECTORS – RoHS COMPLIANT

DWG NO. P-RJHSE-LEDS REV H

CODE ID NO. 03554 | DWG SIZE C | SCALE NA | SHEET 1 OF 1