

1		2		3		4		5		6		7		8	
				REV.		ECN NO.		DATE		SIGN		DESCRIPTION			
				A		Initial Release		2014-02-08		Fisher		Initial Release			

ALTW

CONFIDENTIAL

2014-02-08

R&D DEPT.

16.2

QC L (mm)

9.6

1

SSL11-J6LJ0-000000

2

W2B Lock

3

Wire

4.8

12.4

#2

#4

#6

#1

#3

#5

Conn. 1

14.2

ALTW

Brown

Red

Orange

Yellow

Green

Blue

6

Blue

藍

5

Green

綠

4

Yellow

黃

3

Orange

橙

2

Red

紅

1

Brown

棕

Conn. 1

Wire Color

Pin Out

UNIT:mm

TOLERANCE

.X

±0.25

.XX

±0.1

.XXX

±0.05

ANGLES

±1°

TITLE

SSL11 WIRE ASS'Y, WITH W2B LOCK

6-POS, JACK TO OPEN

SCALE

3:1

SIZE

A4

SHEET

1

OF

1

REV.

A

WC-REV.

A.9

QC

Inspection item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO

DWG NO

SSL11-J6LJ0-B22AXX

CUSTOMER

ALTW

DRAWN BY

Fisher_Wang

CHECKED BY

Ivan_Lin

APPROVED BY

Kevin_Hu

DATE

2014-02-08

DATE

2014-02-08

DATE

2014-02-08

Notes:

* QC Important Dimensions To Check.

* Housing: Thermoplastic, UL94V-0, Natural White.

* Terminal: Copper Alloy, Gold Plated.

* Hood: Thermoplastic, UL94V-0, Natural White.

* SR Mold: PP, UL94V-0, Natural White.

* W2B Lock: Thermoplastic, UL94V-0, Natural White.

* Wire: UL1430 22AWG, Brown/Red/Orange/Yellow/Green/Blue.

* Wire Length Tolerance: ±5%mm.

01: L=100±20 mm.

02: L=200±20 mm.

04: L=400±25 mm.

Standard Length is 400mm

Wire Length Range(L): 100~9900mm

22: 22AWG

LOCK&LATCH OPTION

B: WITH W2B LOCK

ALTW

DCC. DEPT.

CONFIDENTIAL

2014.02.13

ISSUED

1

2

3

4

5

6

7

8

FWN10702-01-02A1