T4144035081-000 ✔ ACTIVE


M12 Connector

TE Internal #: T4144035081-000

Wire-to-Panel, Circular Connector Plug, 8 Position, Shell Size 18, Sealable, Wire & Cable, Signal, Panel Mount & Board Mount, M12 Connector

View on TE.com >

Connectors > Circular Connectors > Standard Circular Connectors




Connector System: **Wire-to-Panel**

Connector Mounting Type: **Panel Mount & Board Mount**

Number of Positions: **8**

Sealable: **Yes**

Connector & Contact Terminates To: **Wire & Cable**

Features

Product Type Features

Assembly Requirement	Factory Assembled
Circular Connector Shell Type	Metal-Shell
Connector Product Type	Connector Assembly
Assembly Type	Electrical Connector
Connector System	Wire-to-Panel
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Circular Connector Type	Circular Connector Plug
Shell Type	Metal

Configuration Features

Keying & Polarized Position Locations	0
Number of Positions	8
Number of Power Positions	0
Number of Signal Positions	8

Contacts Preloaded	Yes

Electrical Characteristics

Operating Voltage	30 VDC

Body Features

Product Weight	10.13 g[.352 oz]
O-Ring Material	Silicone
Environmental Protection	IP67
Environmental Protection Type	Elastomer Sealed
Primary Product Color	Black
Peripheral Seal Material	Silicone
Shell Plating Material	Nickel
Shell Base Material	Copper Alloy
Circular Connector Insulation Material Type	Polyamide GF
Hermetically Sealed	Yes

Contact Features

Contact Current Rating (Max)	2 A
Reverse Gender	Yes
Circular Connector Contact Type	Pin

Termination Features

Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Mating Retention Type	Threaded Coupling
PCB Mount Retention	With
Panel Mount Feature Type	Screw Nut
Mating Alignment	With
Connector Mounting Type	Panel Mount & Board Mount
Polarization Code	A
Mating Alignment Type	Keyed

Housing Features

Circular Connector Shell Size	18

Dimensions

Panel Thickness (Recommended)	2 – 3 mm[.079 – .118 in]

Usage Conditions

IP Dust Sealing Level	6
IP Water Sealing Level	IP67
Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]

Operation/Application

Circuit Application	Signal
Shielded	No

Industry Standards

UL Flammability Rating	UL 94HB

Packaging Features

Packaging Quantity	120

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量超出标准 Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) SVHC > Threshold: Pb (4% in 74024580) **Article Safe Usage Statements:** Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on

requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Also in the Series | M12 Connector



Connector Hardware(11)



Connector Seals & Cavity Plugs(4)



Standard Circular Connectors(792)

Customers Also Bought



TE Part #802435-SF
FN2030-20-06



TE Part #803749-SF
FN9222-1-06



TE Part #EP3166-000
0026G8424-9



TE Part #487545-5
008 HOUSING FFC RCPT 050CL SR



TE Part #487547-1
FFC RCPT CONTACT .050CL



TE Part #1825027-6
FSMRA2JHA04=R/A,TACT PB SW,260



TE Part #2110304-1
SFP+ 1x1 Cage Assembly, Solder Tail



TE Part #2173239-1
1x3 Cage Assy Bhnd Bzl QSFP28



TE Part #2176070-6
3521 16R 1% 2W



TE Part #4-2176339-8
CRGCQ 0603 82K 1%

Documents

Product Drawings

M12 RA PCB CONN. Male 8P SHIELD

English

CAD Files

Customer View Model

ENG_CVM_CVM_T4144035081-000_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_T4144035081-000_B.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_T4144035081-000_B.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

Application Specification

English

Agency Approvals

UL

English