CUI Devices is now Same Sky! Learn More

same sky

SERIES: TS29 | DESCRIPTION: TACTILE SWITCH

FEATURES

- illuminated
- 5 color options
- through hole



RoHS

SPECIFICATIONS

parameter	conditions/description	min	typ	max	units
rated voltage				12	Vdc
rated current				50	mA
withstanding voltage	for 1 minute		250		Vac
contact resistance	applying load of 2 times operating force at 5 Vdc, 10 mA			100	mΩ
insulation resistance	for 1 minute at 100 Vdc	100			MΩ
operating force		200	300	400	gf
return force		20			gf
actuator travel		0.25	0.35	0.45	mm
operating temperature		-30		80	°C
storage temperature		-40		90	°C
life	at 5 Vdc, 5 mA, 20 cycles/second, 1.5 times operating force		100,000		cycles
vibration	10~55~10 Hz, 1.5 mm amplitude, 2 hours on each XYZ				
flammability rating	see material table				
RoHS	yes				

SOLDERABILITY

parameter	conditions/description	min	typ	max	units
hand soldering	for maximum 3 seconds			350	°C
wave soldering	for maximum 5 seconds			260	°C

PART NUMBER KEY

TS29 - 1212 - 1 - XX - 300 - D

Base Number

LED Color:
WT = white
BL = blue
R = red
G = green
Y = yellow

LED ABSOLUTE MAXIMUM RATINGS (WHITE) (TA=25°C)


parameter	conditions/description	min	typ	max	units
power dissipation (Pd)				18	mW
DC forward current (IF)				5	mA
peak forward current (IFP)	pulse of 1/10 duty and 0.1 ms width			100	mA
reverse voltage (VR)				5	V

LED ELECTRO-OPTICAL CHARACTERISTICS (WHITE) (TA=25°C)


parameter	conditions/description			min	typ	max	units
forward voltage (Vf)	at IF=20 mA				3.2	3.6	V
luminous intensity (Iv)	at IF=20 mA			200	600		mcd
chromacity coodinates	at IF=20 mA	white	X Y	0.285 0.287	0.28 0.29	0.287 0.295	
reverse current (IR)	at VR=5 V					1	μA
viewing angle (2θ1/2)	at IF=20 mA				30		deg

LED ELECTRO-OPTICAL CHARACTERISTIC CURVES (WHITE)


RELATIVE INTENSITY VS. WAVELENGTH




FORWARD CURRENT DERATING CURVE




FORWARD CURRENT VS. FORWARD VOLTAGE




RELATIVE LUMINOUS INTENSITY VS. AMBIENT TEMPERATURE



RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT



RADIATION DIAGRAM



LED ABSOLUTE MAXIMUM RATINGS (BLUE) (TA=25°C)


parameter	conditions/description	min	typ	max	units
power dissipation (Pd)				120	mW
DC forward current (IF)				30	mA
peak forward current (IFP)	pulse of 1/10 duty and 0.1 ms width			100	mA
reverse voltage (VR)				5	V

LED ELECTRO-OPTICAL CHARACTERISTICS (BLUE) (TA=25°C)


parameter	conditions/description	min	typ	max	units
forward voltage (Vf)	at IF=20 mA		3.0	3.2	V
luminous intensity (Iv)	at IF=20 mA	1,000	1,400		mcd
peak wavelength (λp)	at IF=20 mA		460		nm
dominant wave length (λd)	at IF=20 mA	465		470	nm
spectral line half-width (Δλ)	at IF=20 mA		30		nm
viewing angle (2θ1/2)	at IF=20 mA		30		deg

LED ELECTRO-OPTICAL CHARACTERISTIC CURVES (BLUE)


RELATIVE IN TENSITY VS. WAVELENGTH




FORWARD CURRENT DERATING CURVE




FORWARD CURRENT VS. FORWARD VOLTAGE




RELATIVE LUMINOUS INTENSITY VS.AMBIENT TEMPERATURE



RELATIVE LUMINOUS INTENSITY VS.FORWARD CURRENT



RADIATION DIAGRAM



LED ABSOLUTE MAXIMUM RATINGS (RED) (TA=25°C)


parameter	conditions/description	min	typ	max	units
power dissipation (P_d)				52	mW
DC forward current (I_F)				20	mA
peak forward current (I_{FP})	pulse of 1/10 duty and 0.1 ms width			100	mA
reverse voltage (V_R)				5	V

LED ELECTRO-OPTICAL CHARACTERISTICS (RED) (TA=25°C)


parameter	conditions/description	min	typ	max	units
forward voltage (V_f)	at I_F=20 mA		2.0	2.6	V
luminous intensity (I_v)	at I_F=20 mA	2,600	3,000		mcd
reverse current (I_R)	at V_R=5 V			100	µA
peak wavelength (λp)	at I_F=20 mA		622		nm
dominant wave length (λd)	at I_F=20 mA	620		625	nm
spectral line half-width ($\Delta\lambda$)	at I_F=20 mA		20		nm
viewing angle ($2\theta_{1/2}$)	at I_F=20 mA		30		deg

LED ELECTRO-OPTICAL CHARACTERISTIC CURVES (RED)


RELATIVE IN TENSITY VS. WAVELENGTH




FORWARD CURRENT DERATING CURVE




FORWARD CURRENT VS. FORWARD VOLTAGE




RELATIVE LUMINOUS INTENSITY VS.AMBIENT TEMPERATURE



RELATIVE LUMINOUS INTENSITY VS.FORWARD CURRENT



RADIATION DIAGRAM



LED ABSOLUTE MAXIMUM RATINGS (GREEN) (TA=25°C)


parameter	conditions/description	min	typ	max	units
power dissipation (Pd)				72	mW
DC forward current (IF)				20	mA
peak forward current (IFP)	pulse of 1/10 duty and 0.1 ms width			100	mA
reverse voltage (VR)				5	V

LED ELECTRO-OPTICAL CHARACTERISTICS (GREEN) (TA=25°C)


parameter	conditions/description	min	typ	max	units
forward voltage (Vf)	at IF=20 mA		3.2	3.6	V
luminous intensity (Iv)	at IF=20 mA	14,500	15,000		mcd
reverse current (IR)	at VR=5 V			1	µA
peak wavelength (λp)	at IF=20 mA		515		nm
dominant wave length (λd)	at IF=20 mA	510		525	nm
spectral line half-width (Δλ)	at IF=20 mA		30		nm
viewing angle (2θ1/2)	at IF=20 mA		30		deg

LED ELECTRO-OPTICAL CHARACTERISTIC CURVES (GREEN)


RELATIVE IN TENSITY VS. WAVELENGTH




FORWARD CURRENT DERATING CURVE




FORWARD CURRENT VS. FORWARD VOLTAGE




RELATIVE LUMINOUS INTENSITY VS.AMBIENT TEMPERATURE



RELATIVE LUMINOUS INTENSITY VS.FORWARD CURRENT



RADIATION DIAGRAM



LED ABSOLUTE MAXIMUM RATINGS (YELLOW) (TA=25°C)


parameter	conditions/description	min	typ	max	units
power dissipation (Pd)				60	mW
DC forward current (IF)				20	mA
peak forward current (IFP)	pulse of 1/10 duty and 0.1 ms width			100	mA
reverse voltage (VR)				5	V

LED ELECTRO-OPTICAL CHARACTERISTICS (YELLOW) (TA=25°C)


parameter	conditions/description	min	typ	max	units
forward voltage (Vf)	at IF=20 mA		2.0	2.3	V
luminous intensity (Iv)	at IF=20 mA	500	800		mcd
peak wavelength (λp)	at IF=20 mA		589		nm
dominant wave length (λd)	at IF=20 mA	587	590	593	nm
spectral line half-width (Δλ)	at IF=20 mA		30		nm
viewing angle (2θ1/2)	at IF=20 mA		30		deg

LED ELECTRO-OPTICAL CHARACTERISTIC CURVES (YELLOW)


RELATIVE IN TENSITY VS. WAVELENGTH




FORWARD CURRENT DERATING CURVE




FORWARD CURRENT VS. FORWARD VOLTAGE




RELATIVE LUMINOUS INTENSITY VS.AMBIENT TEMPERATURE



RELATIVE LUMINOUS INTENSITY VS.FORWARD CURRENT




RADIATION DIAGRAM





MECHANICAL DRAWING

units: mm
tolerance: ±0.4 mm
unless otherwise noted


ITEM	DESCRIPTION	MATERIAL	PLATING/COLOR
1	terminals	H62	silver
2	base	PA66 (UL94HB)	black
3	contacts	SUS	silver
4	burron pad	PA66 (UL94HB)	black
5	LED		see part number key
6	cover	PA66 (UL94HB)	white
7	stem	PC (UL94HB)	red










ACTUATOR POSITION [ ]: MOMENTARY	
NORMAL	DOWN
OFF	[ON]
SCHEMATIC	





POLARITY













Recommended PCB Layout
Top View


PACKAGING

units: mm

Inner Bag Size: 190 x 195 mm
Inner Bog QTY: 100 pcs per box
Carton Size: 430 x 340 x 350 mm
Carton QTY: 7,500 pcs per carton







REVISION HISTORY

rev.	description	date
1.0	initial release	06/14/2023
1.01	CUI Devices rebranded to Same Sky	09/12/2024

The revision history provided is for informational purposes only and is believed to be accurate.

Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.