Common Mode SC Coils, SC-G/GS Series, Small Type

Overview


The KEMET SC-G/GS coils are common mode chokes with a wide variety of characteristics. These toroidal coils are designed with our proprietary ferrite cores and are useful in various noise countermeasure fields.

Applications

- Audio-visual equipment
- Home appliances
- Power supplies

Benefits

- Proprietary 10H ferrite material and equivalents
- Suitable for ≥ 150 kHz range
- Wide variety of sizes and specifications
- Operating temperature range from −40°C to +105°C or +120°C
- UL 94 V–2 or V–0 flame retardant rated cap





Part Number System

SC-	01-		06	G
Series	Rated Current (A)	Thermal Class	Inductance (mH) Minimum	Dimension Code (See Dimensions)
SC	0x = x A Example: 02 = 2 A	Blank = Class A E = Class E	0x = 0.x mH x0 = x.0 mH Examples: 06 = 0.6 mH 20 = 2.0 mH Note: With exceptions, see Table 1 for details.	G GS

© KEMET Electronics Corporation • One East Broward Boulevard
Fort Lauderdale, FL 33301 USA • 954-766-2800 • www.kemet.com


Magnetic Permeability of Ferrite Material

In order to achieve most efficient noise reduction, it is important to select the material according to the target frequency band. Depending on its magnetic permeability, a particular ferrite material will be effective in a certain frequency band. A schematic representation of the relationship between the magnetic permeability of each material and the corresponding effective band range is shown in Figure 1. Materials with higher magnetic permeability are effective in the lower frequency range, while those with lower magnetic permeability are effective in the higher frequency range. Thus, Mn-Zn products are mainly used for reducing conduction noise, while Ni-Zn products are commonly used for radiation noise countermeasures.


The effective frequency range varies depending on core shape, size and number of windings. This frequency dependence of the magnetic permeability as shown in the figure serves for reference purposes only and it should be tested on the actual device to determine its effectiveness.

S18H, S15H, 10H, 7H, 5H, 1400L and 700L are KEMET's proprietary ferrite material names.
Other materials can also be available on request.

Figure 1 - Relationship between the magnetic permeability of each material and its effective frequency range



Dimensions – Millimeters



Part Name	Dimensions (mm)			Pin Pitch[1] (Reference)	
	OD (Maximum)	T (Maximum)	L	a	b
SC-01-06G	17.5	14.0	15±2.0	6	10
SC-01-10G	17.5	14.0	15±2.0	6	10
SC-01-20G	17.5	14.0	15±2.0	6	10
SC-01-30G	17.5	14.0	15±2.0	6	10
SC-01-50G	17.5	14.0	15±2.0	6	10
SC-01-80G	17.5	14.0	15±2.0	6	10
SC-01-E50G	17.5	14.0	15±2.0	6	10
SC-02-06G	17.5	14.0	15±2.0	6	10
SC-02-10G	17.5	14.0	15±2.0	6	10
SC-02-20G	17.5	14.0	15±2.0	6	10
SC-02-30G	17.5	14.0	15±2.0	6	10
SC-03-06G	17.5	14.0	15±2.0	6	10
SC-03-10G	17.5	14.0	15±2.0	6	10
SC-03-E016G	17.5	14.0	15±2.0	10	11
SC-06-01G	17.0	14.0	8±1.5	6	10
SC-01-10GS	15.0	8.5	15±2.0	6	8
SC-01-20GS	15.0	8.5	15±2.0	6	8
SC-02-10GS	15.0	8.5	15±2.0	6	8
SC-03-05GS	15.0	8.5	15±2.0	6	8

**Pin pitch values are for reference only. Values are not guaranteed.*

Environmental Compliance

All KEMET AC line filters are RoHS Compliant.

© KEMET Electronics Corporation • One East Broward Boulevard
Fort Lauderdale, FL 33301 USA • 954-766-2800 • www.kemet.com

Performance Characteristics

Item	Performance Characteristics
Rated Voltage	250 VAC/VDC
Withstanding Voltage	2, 400 V (2 seconds, between lines)
Insulation Resistance	> 100 MΩ at 500 VDC (between lines)
Rated Current Range	1 – 6 A
Rated Inductance Range	0.105 – 8.0 mH minimum
Inductance Measurement Condition	1 kHz, 10 kHz, and 100 kHz
Thermal Class	A (105°C) and E (120°C)
Operating Temperature Range	−40°C to +105°C (include self temperature rise) and −40°C to +120°C (include self temperature rise)

Table 1 – Ratings & Part Number Reference

Part Number	Rated Current AC (A)	Inductance (mH) Minimum	DC Resistance/ Line (mΩ) Maximum	Temperature Rise (K) Maximum	Wire Diameter (mm)	Marking	Thermal Class	Weight (g) Approximate
SC-01-06G	1	0.6000 [3]	60.00	40.0	0.40	106	A (105°C)	5.0
SC-01-10G	1	1.0000 [3]	70.00	40.0	0.40	110	A (105°C)	5.0
SC-01-20G	1	2.0000 [3]	100.00	40.0	0.40	120	A (105°C)	5.0
SC-01-30G	1	3.0000 [3]	120.00	40.0	0.40	130	A (105°C)	6.0
SC-01-50G	1	5.0000 [3]	150.00	40.0	0.40	150	A (105°C)	7.0
SC-01-80G	1	8.0000 [3]	300.00	40.0	0.35	180	A (105°C)	6.0
SC-01-E50G	1	5.0000 [1]	150.00	40.0	0.40	150	E (120°C)	4.9
SC-01-E100G	**1**	**10.0000**	**350.00**	**40.0**	**0.35**	**100**	**E (120°C)**	**6.0**
SC-01-E121G	**1**	**12.0000**	**400.00**	**40.0**	**0.35**	**121**	**E (120°C)**	**6.0**
SC-01-E150G	**1**	**15.0000**	**450.00**	**40.0**	**0.35**	**–**	**E (120°C)**	**6.0**
SC-02-06G	2	0.6000 [3]	50.00	40.0	0.50	206	A (105°C)	6.0
SC-02-10G	2	1.0000 [3]	50.00	40.0	0.50	210	A (105°C)	7.0
SC-02-20G	2	2.0000 [3]	70.00	40.0	0.50	220	A (105°C)	8.0
SC-02-30G	2	3.0000 [3]	85.00	40.0	0.50	230	A (105°C)	9.0
SC-03-06G	3	0.6000 [3]	30.00	40.0	0.60	306	A (105°C)	7.0
SC-03-10G	3	1.0000 [3]	35.00	40.0	0.60	310	A (105°C)	8.0
SC-03-E016G	3	0.1638 [2]	8.51	17.5	0.70	-	E (120°C)	4.5
SC-06-01G	6	0.1050 [1]	10.00	40.0	0.65	-	A (105°C)	3.8
SC-01-10GS	1	1.0000 [1]	130.00	40.0	0.30	–	A (105°C)	2.0
SC-01-20GS	1	2.0000 [1]	180.00	40.0	0.30	–	A (105°C)	2.0
SC-02-10GS	2	1.0000 [1]	80.00	40.0	0.40	–	A (105°C)	3.0
SC-03-05GS	3	0.5000 [1]	45.00	45.0	0.45	–	A (105°C)	3.0

Parts in bold are not for new design.


[1] Inductance Measurement Condition: 1 kHz

[2] Inductance Measurement Condition: 10 kHz


[3] Inductance Measurement Condition: 100 kHz

Frequency Characteristics


SC-01-06G




SC-01-10G




SC-01-20G




SC-01-30G




SC-01-50G




SC-01-80G



SC-01-E50G




SC-02-06G




Frequency Characteristics cont.


SC-02-10G




SC-02-20G




SC-02-30G




SC-03-06G




SC-03-10G




SC-03-E016G



SC-06-01G




SC-01-10GS




Frequency Characteristics cont.


SC-01-20GS



SC-02-10GS



SC-03-05GS



Packaging

Type	Packaging Type	Pieces Per Box
SC-G	Tray	1,300
SC-03-E016G		550
SC-GS	Bulk	3,000

Handling Precautions

Precautions for product storage
AC Line Filters should be stored in normal working environments. While the chokes themselves are quite robust in other environments, solderability will be degraded by exposure to high temperatures, high humidity, corrosive atmospheres, and long term storage.

KEMET recommends that maximum storage temperature not exceed 40°C and maximum storage humidity not exceed 70% relative humidity. Atmospheres should be free of chlorine and sulfur bearing compounds. Temperature fluctuations should be minimized to avoid condensation on the parts. Avoid storage near strong magnetic fields, as this might magnetize the product.

For optimized solderability, AC line filters stock should be used promptly and preferably within 6 months of receipt.

Product temperature rise values
The values listed for temperature rise are the result of self-heating in wires when the rated current (commercial frequency) is applied.

When using the product, check and evaluate the value of the core temperature rise under actual operating conditions.

KEMET Electronics Corporation Sales Offices

For a complete list of our global sales offices, please visit www.kemet.com/sales.

Disclaimer

YAGEO Corporation and its affiliates do not recommend the use of commercial or automotive grade products for high reliability applications or manned space flight.

All product specifications, statements, information and data (collectively, the "Information") in this datasheet are subject to change. The customer is responsible for checking and verifying the extent to which the Information contained in this publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

Statements of suitability for certain applications are based on KEMET Electronics Corporation's ("KEMET") knowledge of typical operating conditions for such applications, but are not intended to constitute – and KEMET specifically disclaims – any warranty concerning suitability for a specific customer application or use. The Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by KEMET with reference to the use of KEMET's products is given gratis, and KEMET assumes no obligation or liability for the advice given or results obtained.

Although KEMET designs and manufactures its products to the most stringent quality and safety standards, given the current state of the art, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards (such as installation of protective circuitry or redundancies) in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage.

Although all product–related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated or that other measures may not be required.

When providing KEMET products and technologies contained herein to other countries, the customer must abide by the procedures and provisions stipulated in all applicable export laws and regulations, including without limitation the International Traffic in Arms Regulations (ITAR), the US Export Administration Regulations (EAR) and the Japan Foreign Exchange and Foreign Trade Act.

KEMET is a registered trademark of KEMET Electronics Corporation.