Honeywell | Sensing and Control

V7-1C17D8-294



Actual product appearance may vary.

V7 Series Miniature Basic Switch, Single Pole Double Throw Circuitry, 15 A at 250 Vac, Simulated Roller Lever Actuator (Corrosion Resistant), 0,89 N [3.2 oz] Maximum Operating Force, Silver Contacts, Quick Connect Termination

click here to download Hi-Res image

Product Specifications

Switch Type	MICRO SWITCH™ Miniature 15,9 mm H x 10,2 mm W x 28,8 mm L [0.63 in H x 0.4 in W x 1.14 in L]
Sealed	No
Ampere Rating	15 A
Circuitry	SPDT
Actuator	Simulated Roller Lever
Termination	Quick Connect
Operating Temperature	-40 °C to 82 °C [-40 °F to 180 °F]
Voltage	250 Vac
Actuator Length	26,16 mm [1.03 in]
Contact Type	Silver
Operating Force (OF)	0,89 N [3.2 oz] max.
Release Force	0,09 N [0.31 oz] min.
Pretravel (PT)	3,07 mm [0.121 in] max.
Overtravel (OT)	1,73 mm [0.068 in] min.
Differential Travel (DT)	0,69 mm [0.027 in] max.
Operating Position (OP)	20,5 mm ±1,27 mm [0.806 ±0.050 in]
Housing Material	PCT Polyester Thermoplastic
Agency Approvals and Standards	UL, CSA
Mounting Centers	22,2 mm [0.88 in]
Tightening Torque	0,56 N m [5.0 in lb]
Weight	8 g [0.3 oz]
Package Height	15,9 mm [0.63 in]
Package Width	10,3 mm [0.40 in]
Package Length	27,8 mm [1.09 in]
Comment	Corrosion Resistant Actuator; CE: 61058-1; UL: E12252; CSA: LR41370
Availability	Global
UNSPSC Code	39122209
UNSPSC Commodity	39122209 Snap switches
Series Name	V7